

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

### Section 1: Identification

Product name : Sikafloor®-262 AS N Part A

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

#### Recommended use of the chemical and restrictions on use

Product use : Epoxy coating

### Section 2: Hazard identification

#### GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Hazardous to the aquatic environment - chronic hazard : Category 2

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P391 Collect spillage.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	25068-38-6	$\geq 20$ -< 25
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )	9003-36-5	$\geq 2.5$ -< 10

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	3101-60-8	>= 2.5 -< 10
benzyl alcohol	100-51-6	>= 1 -< 10
xylene	1330-20-7	>= 0.1 -< 1

### Section 4: First-aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Allergic reactions  
Excessive lachrymation  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.
- Notes to physician : Treat symptomatically.

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version 1.0	Revision Date: 2023/04/25	SDS Number: 000000118384	Date of last issue: - Date of first issue: 2023/04/25
----------------	------------------------------	-----------------------------	--

---

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 3Z

---

### Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

---

### Section 7: Handling and storage

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

---

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m <sup>3</sup>	NZ OEL
Further information: Ototoxin				

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : various
- Odour : epoxy-like

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version 1.0      Revision Date: 2023/04/25      SDS Number: 000000118384      Date of last issue: -  
Date of first issue: 2023/04/25

---

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 101 °C (214 °F)  
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.68 g/cm<sup>3</sup> (20 °C (68 °F))

Solubility(ies)

    Water solubility : insoluble

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds (VOC) content : 53.0 g/l

---

### Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

---

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

### Section 11: Toxicological information

#### Acute toxicity

Not classified based on available information.

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

#### **p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3,466 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 6,000 mg/kg

#### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

### Respiratory sensitisation

Not classified based on available information.

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

---

## Section 12: Ecological information

### Ecotoxicity

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

#### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

#### **xylene:**

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
icity) Exposure time: 56 d

Toxicity to daphnia and other : NOEC (Daphnia (water flea)): 1.17 mg/l  
aquatic invertebrates (Chron- Exposure time: 7 d  
ic toxicity)

#### **Persistence and degradability**

No data available



# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version  
1.0

Revision Date:  
2023/04/25

SDS Number:  
000000118384

Date of last issue: -  
Date of first issue: 2023/04/25

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## Section 13: Disposal considerations

### Disposal methods

Waste from residues : Send to a licensed waste management company.  
  
The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
  
Do not re-use empty containers.

---

## Section 14: Transport information

### International Regulations

#### IATA-DGR

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

#### IMDG-Code

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version 1.0      Revision Date: 2023/04/25      SDS Number: 000000118384      Date of last issue: -  
Date of first issue: 2023/04/25

---

Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### NZS 5433

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9  
Hazchem Code : 3Z

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### HSNO Approval Number

HSR002670

### HSW Controls

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

---

## Section 16: Other information

Revision Date : 2023/04/25  
Date format : dd.mm.yyyy

### Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

---

# SAFETY DATA SHEET

## Sikafloor®-262 AS N Part A



Version 1.0	Revision Date: 2023/04/25	SDS Number: 000000118384	Date of last issue: - Date of first issue: 2023/04/25
----------------	------------------------------	-----------------------------	--

---

NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN