Sika BlackSeal Elastic



Version 5.1	Revision Date: 2024/11/24		SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
Section 1:	Identification			
Produ	ct name	:	Sika BlackSeal Elastic	
Manu	facturer or supplier's o	deta	ils	
Comp	any	:	Sika (NZ) Ltd. 85-91 Patiki Road Avondale Auckland AKL 1026	
Telepl	hone	:	+64 9 820 2900	
Emerg	gency telephone numbe	r :	0800 734 607	
E-mai	l address	:	info@nz.sika.com	
Telefa	ix	:	+64 9 828 4091	
Reco	mmended use of the cl	hem	ical and restrictions on use	
Produ	ct use	:	Bituminous coating	
Section 2:	Hazard identification			
GHS (Classification			
	ensitisation	:	Category 1	

GHS label elements

Hazard pictograms

Hazard statements

Precautionary statements

:

:

:

Signal word

Warning

H317 May cause an allergic skin reaction. :

Prevention:

P261 Avoid breathing mist or vapours. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Sika BlackSeal Elastic



Version	Revision Date:	SDS Number:	Date of last issue: 2022/10/20
5.1	2024/11/24	100000021410	Date of first issue: 2018/08/19

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification None known.

Section 3: Composition/information on ingredients

Substance / Mixture	:	Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Asphalt	8052-42-4	>= 30 -< 50
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5	>= 0.1 -< 0.25

Section 4: First-aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. sensitising effects Allergic reactions See Section 11 for more detailed information on health effects and symptoms.
Notes to physician	:	Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

Sika BlackSeal Elastic



Version 5.1	Revision Date: 2024/11/24		SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
			cumstances and the surrou	unding environment.
Hazar ucts	rdous combustion prod-	:	No hazardous combustion	products are known
Speci ods	fic extinguishing meth-	:	Standard procedure for che	emical fires.
Speci	al protective equipment efighters	:	In the event of fire, wear se	elf-contained breathing apparatus.
Section 6:	Accidental release me	as	ures	
tive e	nal precautions, protec- quipment and emer- / procedures	:	Use personal protective eq Deny access to unprotecte	
Enviro	onmental precautions	:	Do not flush into surface w	ater or sanitary sewer system.
	ods and materials for inment and cleaning up	:	Soak up with inert absorbe acid binder, universal binde Keep in suitable, closed co	
Section 7:	Handling and storage			
	e on protection against nd explosion	:	Normal measures for preve	entive fire protection.
Advic	e on safe handling	:	section 8). Do not get in eyes, on skin For personal protection see Persons with a history of sk ma, allergies, chronic or re- not be employed in any pro- used. Smoking, eating and drinki plication area.	
Hygie	ne measures	:	practice. When using do not eat or d When using do not smoke.	
Condi	itions for safe storage	:		ed in a dry and well-ventilated

Sika BlackSeal Elastic



Version	Revision Date:	SDS Number:	Date of last issue: 2022/10/20
5.1	2024/11/24	10000021410	Date of first issue: 2018/08/19

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Asphalt	8052-42-4	WES-TWA (Fumes)	0.5 mg/m3	NZ OEL
	Further information: Skin absorption			

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.

Section 9: Physical and chemical properties

Appearance	:	liquid paste
Colour	:	brown
Odour	:	slight
Odour Threshold	:	No data available
рН	:	ca. 11 (20 °C (68 °F))
Melting point/freezing point	:	>= 0 °C (32 °F)
Boiling point/boiling range	:	ca. 100 °C (212 °F)
Flash point	:	> 232 °C (450 °F) (Method: closed cup)

Sika BlackSeal Elastic



Version 5.1	Revision Date: 2024/11/24		SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
Evap	oration rate	:	No data available	
Flam	mability (solid, gas)	:	No data available	
	er explosion limit / Upper nability limit	:	No data available	
	er explosion limit / Lower nability limit	:	No data available	
Vapo	our pressure	:	< 0.75 mmHg (180 °C (356 °	°F))
Relat	tive vapour density	:	No data available	
Dens	ity	:	ca. 1.03 g/cm3 (20 °C (68 °F	-))
	bility(ies) /ater solubility	:	dispersible	
S	olubility in other solvents	:	No data available	
	tion coefficient: n- nol/water	:	No data available	
	-ignition temperature	:	No data available	
Decc	mposition temperature	:	No data available	
Visco Vi	osity iscosity, dynamic	:	22,500 mPa.s (ca. 25 °C (77	7°F))
Vi	iscosity, kinematic	:	No data available	
Explo	osive properties	:	No data available	
Oxidi	zing properties	:	No data available	
	ile organic compounds C) content	:	no VOC contained	
Section 1	0: Stability and reactivit	ÿ		
Read	tivity	:	No dangerous reaction know	vn under conditions of normal use.
Cher	nical stability	:	The product is chemically st	able.
Poss tions	ibility of hazardous reac-	:	No hazards to be specially n	nentioned.
•				

Conditions to avoid:No data availableIncompatible materials:No data available

Sika BlackSeal Elastic



ersion 1	Revision Date: 2024/11/24	SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
Hazar produc	dous decomposition cts	: No hazardous decomposi	tion products are known.
Section 11	: Toxicological informa	ation	
	toxicity assified due to lack of da	ta.	
	onents:		
1,2-be	enzisothiazol-3(2H)-one oral toxicity	(BIT): : LD50 Oral (Rat): 450 mg/k	g
Acute	inhalation toxicity	: LC50: 0.21 mg/l Exposure time: 4 h Test atmosphere: dust/mis Method: OECD Test Guide	
	corrosion/irritation assified due to lack of da	ta.	
	us eye damage/eye irrit assified due to lack of da		
Respi	ratory or skin sensitisa	tion	
	sensitisation ause an allergic skin rea	ction.	
Respi	ratory sensitisation		
	onents: enzisothiazol-3(2H)-one sment	(BIT): : May cause sensitisation by	/ skin contact.
Chron	ic toxicity		
	cell mutagenicity assified due to lack of da	ta.	
	nogenicity assified due to lack of da	ta.	
-	ductive toxicity assified due to lack of da	ta.	
	- single exposure assified due to lack of da	ta.	
	- repeated exposure assified due to lack of da		

Sika BlackSeal Elastic



ersion I	Revision Date: 2024/11/24	SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
-	ation toxicity assified due to lack of da	ta.	
ection 12	: Ecological information	n	
Ecoto	xicity		
Comp	onents:		
Toxicit	enzisothiazol-3(2H)-one ty to daphnia and other c invertebrates	 (BIT): EC50 (Daphnia (water flea Exposure time: 48 h 	a)): 3 mg/l
icity)	tor (Acute aquatic tox- tor (Chronic aquatic y)	: 1 : 1	
	stence and degradabilit ta available	у У	
	cumulative potential ta available		
	i ty in soil ta available		
Other	adverse effects		
Produ Additio matior	onal ecological infor-	: There is no data available	for this product.
ection 13	: Disposal consideration	ons	
Dispo	sal methods		
Waste	from residues	: Send to a licensed waste r	management company.
		Do not contaminate ponds cal or used container.	, waterways or ditches with chemi-
Conta	minated packaging	: Empty remaining contents Dispose of as unused proc	
		Do not re-use empty conta	

Section 14: Transport information

International Regulations	
IATA-DGR UN/ID No.	: Not applicable

Sika BlackSeal Elastic



	Durisian Data			
Versio 5.1	on Revision Date: 2024/11/24		SDS Number: 10000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19
5.1	2024/11/24		10000021410	Date of first issue. 2010/00/19
	Proper shipping name		Not applicable	
	Class Subsidiary risk		Not applicable	
			Not applicable	
	Packing group		Not applicable	
	Labels		Not applicable	
	Packing instruction (cargo aircraft)		Not applicable	
	Packing instruction (passen- ger aircraft)	:	Not applicable	
	IMDG-Code			
	UN number		Not applicable	
	Proper shipping name	:	Not applicable	
	Class		Not applicable	
	Subsidiary risk		Not applicable	
	Packing group		Not applicable	
	Labels		Not applicable	
	EmS Code Marine pollutant		Not applicable	
			Not applicable	
	Transport in bulk according	l to	Annex II of MARPOL 73/78 and	the IBC Code
	Not applicable for product as	sup	plied.	
	National Regulations			
	NZS 5433			
	UN number		Not applicable	
	Proper shipping name		Not applicable	
	Class	:	Not applicable	
	Subsidiary risk	:	Not applicable	
	Packing group	:	Not applicable	
			Not oppliaable	

Special precautions for user

Not applicable

Hazchem Code

Labels

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

: Not applicable

: Not applicable

HSNO Approval Number

HSR002544 Construction Products Subsidiary Hazard Group Standard

Tolerable Exposure Limits (TEL) Not applicable

Environmental Exposure Limits (EEL) Not applicable

Sika BlackSeal Elastic



Version 5.1	Revision Date: 2024/11/24		SDS Number: 100000021410	Date of last issue: 2022/10/20 Date of first issue: 2018/08/19	
Certifie Tracki		ce not	required.	es) Regulations 2017, for further infor-	
The co NZIoC	• •		are reported in the follow On the inventory, or in comp	-	
Section 16	: Other information				
Revisi Date fo	on Date ormat		2024/11/24 dd.mm.yyyy		
Full te	ext of other abbreviat	ions			
NZ OE	EL		New Zealand. Workplace Ex c Contaminants	xposure Standards for Atmospher-	
-	EL / WES-TWA		Workplace Exposure Standard - Time Weighted average		
ADG ADR		: 1	Australian Dangerous Goods Code. European Agreement concerning the International Carriage of Dangerous Goods by Road		
CAS		: (: Chemical Abstracts Service		
DNEL			: Derived no-effect level		
EC50 GHS			: Half maximal effective concentration		
IATA			: Globally Harmonized System : International Air Transport Association		
IMDG			: International Maritime Code for Dangerous Goods		
LD50		:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
LC50		: I 4	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)		
MARP	OL	: İ	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL			: Occupational Exposure Limit		
PBT			: Persistent, bioaccumulative and toxic		
PNEC REAC		: ; i	and of the Council of 18 Dec stration, Evaluation, Author	ration 006 of the European Parliament cember 2006 concerning the Reg- isation and Restriction of Chemi- a European Chemicals Agency	
SVHC			Substances of Very High Co		
vPvB			/ery persistent and very bio		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Sika BlackSeal Elastic



Version 5.1 2024/11/24

Revision Date:

SDS Number: 10000021410 Date of last issue: 2022/10/20 Date of first issue: 2018/08/19

Changes as compared to previous version !

NZ / EN