

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Section 1: Identification

Product name : Sika Boom-G

Product code : 100000030830

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

Recommended use of the chemical and restrictions on use

Product use : Polyurethane foam

Section 2: Hazard identification

GHS Classification

Flammable aerosols : 2.1.2A

Skin irritation : 6.3A

Eye irritation : 6.4A

Respiratory sensitisation : 6.5A

Skin sensitisation : 6.5B

Carcinogenicity : 6.7B

Specific Target Organ Toxicity (Inhalation) : 6.9B

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust or mist.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P321 Specific treatment (see supplemental first aid instructions on this label).
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	>= 10 -< 20
dimethyl ether	115-10-6	>= 1 -< 10
isobutane	75-28-5	>= 1 -< 10

Section 4: First-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Asthmatic appearance
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray jet
Dry powder
Foam
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : 2YE
-

Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Allow to solidify, use mechanical handling equipment.
-

Section 7: Handling and storage

- Advice on protection against fire and explosion : Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Do not spray on a naked flame or any incandescent material.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
-

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Follow standard hygiene measures when handling chemical products

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	WES-TWA	0.02 mg/m ³ (NCO)	NZ OEL
		Further information: Skin sensitiser, Respiratory sensitiser		
		WES-STEL	0.07 mg/m ³ (NCO)	NZ OEL
dimethyl ether	115-10-6	WES-TWA	400 ppm 766 mg/m ³	NZ OEL
		WES-STEL	500 ppm 958 mg/m ³	NZ OEL
isobutane	75-28-5	STEL	1,000 ppm	ACGIH

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : aerosol
- Colour : various
- Odour : ether-like
- Odour Threshold : No data available
- pH : Not applicable substance/mixture reacts with water
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 5100 hPa
- Relative vapour density : No data available
- Density : ca. 0.948 g/cm³ (20 °C (68 °F))
- Solubility(ies)
Water solubility : No data available

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 19.53% w/w

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.
Formation of dangerous fumes during use.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

Section 13: Disposal considerations

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

NZS 5433

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Hazchem Code : 2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002517

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / STEL : Short-term exposure limit
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEEL : Workplace Exposure Standard - Short-Term Exposure Limit
ADG : Australian Dangerous Goods Code.
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods

SAFETY DATA SHEET

Sika Boom-G



Version
2.0

Revision Date:
2021/10/07

SDS Number:
100000030830

Date of last issue: 2020/11/18
Date of first issue: 2020/11/18

LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN