Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Section 1: Identification

Product name : Sikadur-51 Part (B)

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Product is not intended for consumer use, Sealant/adhesive

Section 2: Hazard identification

GHS Classification

Skin corrosion/irritation : Category 1C

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Hazardous to the aquatic environment - chronic hazard

Category 3

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Phenol, methylstyrenated	68512-30-1	>= 10 -< 20
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	25513-64-8	>= 10 -< 20
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 -< 5
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 3 -< 5
benzyl alcohol	100-51-6	>= 1 -< 10
Reaction product of BADGE with IPDA and	Not Assigned	>= 1 -< 2.5
TMDA		

Section 4: First-aid measures

General advice : Move out of dangerous area.

Sikadur-51 Part (B)



Version Revision Date: SDS Number: Date of last issue: 2022/06/28 2022/09/01 000000022063 Date of first issue: 2017/12/19 5.0

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

Small amounts splashed into eyes can cause irreversible tis-In case of eye contact

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

Clean mouth with water and drink afterwards plenty of water. If swallowed

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Sikadur-51 Part (B)



SDS Number: Date of last issue: 2022/06/28 Version **Revision Date:** 000000022063 Date of first issue: 2017/12/19 2022/09/01 5.0

Hazchem Code 2X

Section 6: Accidental release measures

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : paste

Colour : black

Odour : amine-like

Odour Threshold : No data available

pH : ca. 11.2

Concentration: 500 g/l 50 %

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : $> 101 \, ^{\circ}\text{C} (214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : ca. 0.1 hPa

Relative vapour density : No data available

Density : ca. 1.7 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

45 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit Assessment : Corrosive

Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit

Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae/aquatic :

plants m

: EC50 (Scenedesmus capricornutum (fresh water algae)): 29.5

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

: LC50 (Leuciscus idus (Golden orfe)): 174 mg/l

icity)

Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10

plants - 100 mg/l

Exposure time: 72 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic

plants r

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 3259

Proper shipping name : Amines, solid, corrosive, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, trime-

thylhexane-1,6-diamine)

Class : 8 Packing group : III

Labels : Corrosive Packing instruction (cargo : 864

aircraft)

Packing instruction (passen-

860

ger aircraft)

IMDG-Code

UN number : UN 3259

9/11

Sikadur-51 Part (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/28

 5.0
 2022/09/01
 000000022063
 Date of first issue: 2017/12/19

Proper shipping name : AMINES, SOLID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, trimethylhex-

ane-1,6-diamine)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 3259

Proper shipping name : AMINES, SOLID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, trime-

thylhexane-1,6-diamine)

Class : 8
Packing group : III
Labels : 8
Hazchem Code : 2X

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002658

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : Not in compliance with the inventory

Section 16: Other information

Full text of other abbreviations

Sikadur-51 Part (B)



Version 5.0	Revision Date: 2022/09/01		SDS Number: 000000022063	Date of last issue: 2022/06/28 Date of first issue: 2017/12/19	
ADG ADR		:	Australian Dangerous Goods Code. European Agreement concerning the International Carriage of Dangerous Goods by Road		
CAS		:	Chemical Abstracts Service		
DNEL		:	Derived no-effect level		
EC50		:	Half maximal effective concentration		
GHS		:	Globally Harmonized System		
IATA		:	International Air Transport Association		
IMDG		:	International Maritime Code for Dangerous Goods		
LD50		:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
LC50		:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)		
MARPO	L	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL		: Occupational Exposure Limit			
PBT		:	: Persistent, bioaccumulative and toxic		
PNEC		:	Predicted no effect concentration		
REACH		:	Regulation (EC) No 1907/2006 of and of the Council of 18 Decembe istration, Evaluation, Authorisation cals (REACH), establishing a Euro	r 2006 concerning the Regard and Restriction of Chemi-	
SVHC vPvB		:	Substances of Very High Concern Very persistent and very bioaccum		
AL AD		•	very persistent and very bloaccuit	lulative	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN