

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

### Section 1: Identification

Product name : Sika Damp Stop - Part A

Product code : 000000607844

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026  
Telephone : +64 9 820 2900  
Emergency telephone number : 0800 734 607  
Telefax : +64 9 828 4091  
E-mail address : info@nz.sika.com

### Section 2: Hazard identification

#### GHS Classification

Skin irritation : 6.3A

Eye irritation : 6.4A

Skin sensitisation : 6.5B

Germ cell mutagenicity : 6.6B

Aquatic toxicity (Acute or Chronic) : 9.1B

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H341 Suspected of causing genetic defects.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P391 Collect spillage.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100)	25068-38-6	$\geq 20$ -< 30
2,3-epoxypropyl neodecanoate	26761-45-5	$\geq 2.5$ -< 10
zinc oxide	1314-13-2	$\geq 0.1$ -< 0.25
diuron (ISO)	330-54-1	$\geq 0.025$ -< 0.1
pyrithione zinc	13463-41-7	$\geq 0.0025$ -< 0.025
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1	$\geq 0.0025$ -< 0.025

## Section 4: First-aid measures

General advice : Move out of dangerous area.  
Consult a physician.

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

---

Show this safety data sheet to the doctor in attendance.

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Allergic reactions  
Excessive lachrymation  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of causing genetic defects.
- Notes to physician : Treat symptomatically.
- 

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- 

### Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency measures : Use personal protective equipment.  
Deny access to unprotected persons.
-

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

gency procedures

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### Section 7: Handling and storage

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
zinc oxide	1314-13-2	WES-TWA	10 mg/m <sup>3</sup>	NZ OEL

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

		(Respirable dust)		
		WES-TWA (Fume, respirable fraction)	3 mg/m <sup>3</sup>	NZ OEL
		WES-STEL (Fumes)	10 mg/m <sup>3</sup>	NZ OEL
diuron (ISO)	330-54-1	WES-TWA	10 mg/m <sup>3</sup>	NZ OEL
Further information: Carcinogen - suspected human carcinogen				

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : white
- Odour : mild
- Odour Threshold : No data available
- pH : 8.5 - 9.0
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : 100 °C (212 °F)
- Flash point : Not applicable
- Evaporation rate : No data available

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

---

Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.01 hPa
Relative vapour density	:	No data available
Density	:	1.23 - 1.33 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

---

### Section 11: Toxicological information

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **2,3-epoxypropyl neodecanoate:**

Acute oral toxicity : LD50 Oral (Rat): 9,600 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 3,800 mg/kg

##### **zinc oxide:**

Acute oral toxicity : LD50 Oral (Rat): > 15,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **pyrithione zinc:**

Acute oral toxicity : LD50 Oral (Rat): 269 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

#### **Chronic toxicity**

##### **Germ cell mutagenicity**

Suspected of causing genetic defects.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

Not classified based on available information.

##### **STOT - repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

### Aspiration toxicity

Not classified based on available information.

## Section 12: Ecological information

### Ecotoxicity

#### Components:

##### **2,3-epoxypropyl neodecanoate:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.5 mg/l  
Exposure time: 48 h

##### **zinc oxide:**

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0.17 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

##### **diuron (ISO):**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

##### **pyrithione zinc:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.0026 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1,000

M-Factor (Chronic aquatic toxicity) : 10

##### **2-octyl-2H-isothiazole-3-one (OIT):**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.



# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

---

### Section 13: Disposal considerations

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.
- 

### Section 14: Transport information

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

##### IMDG-Code

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

- UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Class : 9  
Packing group : III  
Labels : 9
-

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### HSNO Approval Number

HSR002670 Surface Coatings and Colourants Subsidiary Hazard Group Standard 2017

### HSW Controls

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

## Section 16: Other information

### Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit

# SAFETY DATA SHEET

## Sika Damp Stop - Part A



Version  
6.0

Revision Date:  
2021/01/28

SDS Number:  
000000607844

Date of last issue: 2019/03/21  
Date of first issue: 2017/05/08

---

PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN