Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Section 1: Identification

Product name : Sika MultiPrimer Marine

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Serious eye damage/eye irri-

tation

Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - :

repeated exposure

Category 2

Hazardous to the aquatic

environment - chronic hazard

Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or re-

peated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 50 -< 70
xylene	1330-20-7	>= 1 -< 10
methanol	67-56-1	>= 0.1 -< 1
dibutyltin dilaurate	77-58-7	>= 0.25 -< 1

Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

irritant effects

Excessive lachrymation

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Harmful if swallowed.

Causes serious eve irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Sika MultiPrimer Marine



Revision Date: SDS Number: Version Date of last issue: 2022/05/24 2024/05/15 00000035557 Date of first issue: 2017/11/15 6.0

Dry chemical

Unsuitable extinguishing

media

Water

High volume water jet

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod: :

No hazardous combustion products are known

Specific extinguishing meth-

Use water spray to cool unopened containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 3YE

Section 6: Accidental release measures

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition.

Deny access to unprotected persons.

Prevent product from entering drains. **Environmental precautions**

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

miculite) and place in container for disposal according to local

/ national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure.

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis		
		exposure)	concentration			
ethyl acetate	141-78-6	WES-TWA	200 ppm 720 mg/m3	NZ OEL		
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL		
	Further information: Ototoxin					
methanol	67-56-1	WES-STEL	250 ppm 328 mg/m3	NZ OEL		
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption					
		WES-TWA	200 ppm 262 mg/m3	NZ OEL		

Biological occupational exposure limits

•	-					
Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
xylene	1330-20-7	Methylhip-	Urine	End of	1.5 g/l	NZ BEI
		puric acid		shift		
methanol	67-56-1	Methyl al-	Urine	End of	15 mg/l	NZ BEI
		cohol		shift	-	

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : > 70 °C (158 °F)

Flash point : ca. -4 °C (25 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower :

flammability limit

1 %(V)

Vapour pressure : 99.9915 hPa

Relative vapour density : No data available

Density : ca. 0.98 g/cm3 (20 °C (68 °F))

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : 427 °C

427 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 10 - 20 mPa.s (20 °C (68 °F))

Viscosity, kinematic : $< 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

653 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Peroxides

Strong acids and oxidizing agents

Bases

Hazardous decomposition

products

No hazardous decomposition products are known.

Section 11: Toxicological information

Acute toxicity

Harmful if swallowed.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Section 12: Ecological information

Ecotoxicity

Components:

xylene:

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Sika MultiPrimer Marine



SDS Number: Version **Revision Date:** Date of last issue: 2022/05/24 2024/05/15 00000035557 Date of first issue: 2017/11/15 6.0

icity) Exposure time: 56 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

dibutyltin dilaurate:

Toxicity to fish

LC50 (Fish): 3.1 mg/l Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1 mg/l

aquatic invertebrates

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 48 h

Exposure time: 7 d

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox-

M-Factor (Chronic aquatic

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Section 14: Transport information

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen: 353

ger aircraft)

IMDG-Code

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3

EmS Code : F-E, <u>S-E</u>

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Hazchem Code : 3YE
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002662

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2024/05/15 Date format : dd.mm.yyyy

Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Sika MultiPrimer Marine



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/05/24

 6.0
 2024/05/15
 000000035557
 Date of first issue: 2017/11/15

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN