

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

### Section 1: Identification

Product name : Sika Metalseal Rapid

Product code : 000000609783

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

#### Recommended use of the chemical and restrictions on use

Product use : Adhesive

---

### Section 2: Hazard identification

#### GHS Classification

Flammable Liquids : 3.1B

Acute toxicity (Oral) : 6.1E

Skin irritation : 6.3A

Toxic to Reproduction : 6.8B

Specific Target Organ Toxicity (Inhalation) : 6.9B

Aquatic toxicity (Acute or Chronic) : 9.1C

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H361 Suspected of damaging fertility or the unborn child.

---

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

H371 May cause damage to organs if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

### Other hazards which do not result in classification

None known.

### Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
toluene	108-88-3	>= 10 -< 20
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 10 -< 20
butanone	78-93-3	>= 1 -< 10

### Section 4: First-aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).  
irritant effects  
Aspiration may cause pulmonary oedema and pneumonitis.  
Dermatitis  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs if inhaled.  
May cause damage to organs through prolonged or repeated exposure if inhaled.

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

Notes to physician : Treat symptomatically.

---

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : 3Y

---

### Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

---

### Section 7: Handling and storage

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge  
(which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical  
products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	WES-TWA	50 ppm 188 mg/m <sup>3</sup>	NZ OEL
	Further information: Skin absorption			
butanone	78-93-3	WES-STEL	300 ppm 890 mg/m <sup>3</sup>	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		WES-TWA	150 ppm 445 mg/m <sup>3</sup>	NZ OEL

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
toluene	108-88-3	Toluene	Urine	End of exposure or end of shift	0.03 mg/l	NZ BEI
		o-Cresol	Urine	End of exposure or end of shift	0.3 mg/g Creatinine	NZ BEI
butanone	78-93-3	MEK	Urine	End of shift	2 mg/l	NZ BEI

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- 

### Section 9: Physical and chemical properties

- Appearance : paste
- Colour : green
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : -6 °C (21 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : 7 %(V)
- Lower explosion limit / Lower flammability limit : 1 %(V)
- Vapour pressure : 28.9975 hPa
- Relative vapour density : No data available
-

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

Density	:	1.04 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 25% w/w

---

### Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available

---

### Section 11: Toxicological information

#### Acute toxicity

Not classified based on available information.

#### Components:

##### butanone:

Acute oral toxicity	:	LD50 Oral (Rat): 3,300 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 36 mg/l Exposure time: 4 h

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Chronic toxicity**

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

#### **STOT - single exposure**

May cause damage to organs if inhaled.

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

---

## **Section 12: Ecological information**

### **Ecotoxicity**

No data available

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available



# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

### Other adverse effects

#### Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

---

### Section 13: Disposal considerations

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### Section 14: Transport information

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1133  
Proper shipping name : Adhesives  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1133  
Proper shipping name : ADHESIVES  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

UN number : UN 1133

---

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

Proper shipping name : ADHESIVES  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : 3Y

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### HSNO Approval Number

HSR002662 Surface Coatings and Colourants Flammable Group Standard 2017

### HSW Controls

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

## Section 16: Other information

### Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

# SAFETY DATA SHEET

## Sika Metalseal Rapid



Version  
3.0

Revision Date:  
2021/12/15

SDS Number:  
000000609783

Date of last issue: 2019/12/02  
Date of first issue: 2018/08/26

---

LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN