

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

### Section 1: Identification

Product name : Sika® Aktivator-205

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

### Section 2: Hazard identification

#### GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements :

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
propan-2-ol	67-63-0	>= 90 -<= 100
titanium tetrabutanolat	5593-70-4	>= 1 -< 3

## Section 4: First-aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

---

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Excessive lachrymation  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.
- 

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known  
  
Carbon monoxide
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- 

### Section 6: Accidental release measures

- Personal precautions, protection : Use personal protective equipment.
-

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

---

- tive equipment and emergency procedures : Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 

### Section 7: Handling and storage

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.
- 

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	WES-TWA	400 ppm 983 mg/m <sup>3</sup>	NZ OEL
		WES-STEL	500 ppm 1,230 mg/m <sup>3</sup>	NZ OEL

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butan-1-ol	71-36-3	WES-Ceiling	50 ppm 150 mg/m <sup>3</sup>	NZ OEL
Further information: Skin absorption				

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : colourless

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

---

Odour	:	alcohol-like
Odour Threshold	:	No data available
pH	:	ca. 7 (20 °C (68 °F))
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	82.4 °C (180.3 °F)
Flash point	:	ca. 12 °C (54 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	Upper flammability limit 12 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 2 %(V)
Vapour pressure	:	ca. 45 hPa
Relative vapour density	:	No data available
Density	:	ca. 0.783 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	425 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 2 mPa.s (20 °C (68 °F))
Viscosity, kinematic	:	< 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	795 g/l

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

---

### Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids and oxidizing agents Aldehydes Amines Bases
Hazardous decomposition products	:	butan-1-ol

---

### Section 11: Toxicological information

#### Acute toxicity

Not classified based on available information.

#### Components:

##### propan-2-ol:

Acute oral toxicity	:	LD50 Oral (Rat): < 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 20 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

#### Chronic toxicity

##### Germ cell mutagenicity

Not classified based on available information.

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## **Section 12: Ecological information**

### **Ecotoxicity**

#### **Components:**

##### **propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 9,714 mg/l  
aquatic invertebrates : Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): >  
plants : 100 mg/l  
Exposure time: 72 h

##### **titanium tetrabutanolate:**

Toxicity to fish : LC50 (Fish): 1,825 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1,300 mg/l  
aquatic invertebrates : Exposure time: 48 h

Toxicity to algae/aquatic : EC50: 225 mg/l  
plants : Exposure time: 96 h

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available



# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

### Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

### Section 13: Disposal considerations

#### Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### Section 14: Transport information

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1219  
Proper shipping name : Isopropanol  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1219  
Proper shipping name : ISOPROPANOL  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

UN number : UN 1219  
Proper shipping name : ISOPROPANOL  
Class : 3  
Packing group : II

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

Labels : 3

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### HSNO Approval Number

HSR002662

### HSW Controls

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

## Section 16: Other information

Revision Date : 2022/10/13  
Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit  
NZ OEL / WES-Ceiling : Workplace Exposure Standard - Ceiling

ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

# SAFETY DATA SHEET

## Sika® Aktivator-205



Version  
4.0

Revision Date:  
2022/10/13

SDS Number:  
000000019904

Date of last issue: 2021/03/21  
Date of first issue: 2018/04/06

---

LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN