SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

Section 1: Identification

Product name : SikaTack-MOVE Transportation

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive, Product is not intended for consumer use

Section 2: Hazard identification

GHS Classification

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Hazardous to the aquatic

environment - chronic hazard

Category 3

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist or vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
bis(2-ethylhexyl) adipate	103-23-1	>= 10 -< 20
aliphatic prepolymer (t-polyether based)	138626-39-8	>= 1 -< 10
aliphatic prepolymer (d-polyether based)	39323-37-0	>= 1 -< 10
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2	>= 1 -< 10
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 -< 1
2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-	15625-89-5	>= 0.1 -< 0.25
propanediyl diacrylate		

Section 4: First-aid measures

General advice : Move out of dangerous area.

SikaTack-MOVE Transportation



Version Revision Date: SDS Number: Date of last issue: 2022/09/13 2023/11/14 Date of first issue: 2018/08/16 000000120594 5.0

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

sensitising effects

Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Suspected of causing cancer.

Notes to physician Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Section 6: Accidental release measures

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethylene-1,6- diisocyanate homopolymer	28182-81-2	WES-TWA	0.02 mg/m3 (NCO)	NZ OEL
	Further information: Skin sensitiser, Respiratory sensitiser			
		WES-STEL	0.07 mg/m3 (NCO)	NZ OEL
		WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m3 (NCO)	NZ OEL
		WES-STEL (Inhalable	0.07 mg/m3 (NCO)	NZ OEL

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

		Fraction and Vapour)		
4,4'-methylenediphenyl diiso- cyanate	101-68-8	WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m3 (NCO)	NZ OEL
	Further information: Skin sensitiser, Respiratory sensitiser			
		WES-STEL (Inhalable Fraction and Vapour)	0.07 mg/m3 (NCO)	NZ OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4- Diaminodi- phenyl	Urine	End of exposure or end of shift	10 μg/g creatinine	NZ BEI

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : paste

Colour : black

Odour : odourless

Odour Threshold : No data available

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

: No data available

Boiling point/boiling range : No data available

Flash point : $> 101 \, ^{\circ}\text{C} (214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.2 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

no VOC contained

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

SikaTack-MOVE Transportation



Version Revision Date: SDS Number: Date of last issue: 2022/09/13 2023/11/14 000000120594 Date of first issue: 2018/08/16 5.0

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid No data available

Incompatible materials No data available

Section 11: Toxicological information

Acute toxicity

Not classified due to lack of data.

Components:

bis(2-ethylhexyl) adipate:

Acute oral toxicity LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity LC50 (Rat): > 5.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Hexamethylene-1,6-diisocyanate homopolymer:

: LD50 Oral (Rat): > 2,500 mg/kg Acute oral toxicity

LC50: 1.5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

: LD50 Dermal (Rat): > 2,000 mg/kg Acute dermal toxicity

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

LC50: 1.5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

: LD50 Oral (Rat): 3,680 - 5,000 mg/kg Acute oral toxicity

LD50 Dermal (Rabbit): > 5,000 mg/kg Acute dermal toxicity

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

SikaTack-MOVE Transportation



Version Revision Date: SDS Number: Date of last issue: 2022/09/13 000000120594 Date of first issue: 2018/08/16 2023/11/14 5.0

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Section 12: Ecological information

Ecotoxicity

Components:

bis(2-ethylhexyl) adipate:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 500 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Scenedesmus quadricauda (Green algae)): > 500 mg/l

Exposure time: 72 h

aliphatic prepolymer (t-polyether based):

Toxicity to algae/aquatic

plants

EC50 (algae): 100 mg/l Exposure time: 72 h

NOEC (algae): 100 mg/l Exposure time: 72 h

aliphatic prepolymer (d-polyether based):

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l

NOEC (Daphnia (water flea)): > 100 mg/l

Toxicity to algae/aquatic EC50 (algae): > 100 mg/l

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

plants Exposure time: 72 h

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

1

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.87 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

M-Factor (Acute aquatic tox- :

icity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Section 13: Disposal considerations

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Section 14: Transport information

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

aircraft)

Packing instruction (passen- : Not applicable

ger aircraft)

IMDG-Code

UN number Not applicable Not applicable Proper shipping name Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Marine pollutant : no

Special precautions for user

Not applicable

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002679

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2023/11/14

SikaTack-MOVE Transportation



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/09/13

 5.0
 2023/11/14
 000000120594
 Date of first issue: 2018/08/16

Date format : dd.mm.yyyy

Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN