Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Section 1: Identification

Product name : Sikadur-32 Normal Part B

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Adhesive, Product is not intended for consumer use

Section 2: Hazard identification

GHS Classification

Acute toxicity (Dermal) : Category 4

Skin corrosion/irritation : Category 1C

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 1

Specific target organ toxicity - :

repeated exposure

Category 1

Hazardous to the aquatic

environment - chronic hazard

Category 3

GHS label elements

Hazard pictograms :





Signal word : Danger

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Hazard statements : H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated

exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate-

ly all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Quartz (SiO2)	14808-60-7	>= 30 -< 50	
benzyl alcohol	100-51-6	>= 10 -< 20	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 5 -< 10	
3,6-diazaoctanethylenediamin	112-24-3	>= 5 -< 10	
(1-methylethyl)-1,1'-biphenyl	25640-78-2	>= 2.5 -< 10	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 -< 5	
Adduct IA (epoxy amine adduct)	68609-08-5	>= 2.5 -< 10	

Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Harmful in contact with skin.

Sikadur-32 Normal Part B



Date of last issue: 2022/02/17 Version Revision Date: SDS Number: 2024/02/22 100000007160 Date of first issue: 2017/09/08 5.0

May cause an allergic skin reaction.

Causes serious eye damage.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Notes to physician Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 2X

Section 6: Accidental release measures

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Quartz (SiO2)	14808-60-7	WES-TWA (Respirable dust)	0.05 mg/m3	NZ OEL	
	Further information: Confirmed carcinogen				
		WES-TWA (Respirable	0.05 mg/m3	NZ OEL	
		dust)			

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : paste

Colour : brown

Odour : amine-like

Odour Threshold : No data available

pH : > 11

Concentration: 50 g/l 50 %

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : $> 101 \, ^{\circ}\text{C} (214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.07 hPa

Relative vapour density : No data available

Density : ca. 1.4 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : Not applicable

No data available

Decomposition temperature : No data available

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

259.7 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No hazardous decomposition products are known.

Section 11: Toxicological information

Acute toxicity

Harmful in contact with skin.

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

3,6-diazaoctanethylenediamin:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

7/13

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

(1-methylethyl)-1,1'-biphenyl:

Acute oral toxicity : LD50 Oral (Rat): 4,650 mg/kg

Method: OECD Test Guideline 401

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

Adduct IA (epoxy amine adduct):

Acute oral toxicity : LD50 Oral (Rat, female): 300 - 2,000 mg/kg

Method: OECD Test Guideline 423

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:
Species : Rabbit

Assessment : Corrosive

Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:Species : Rabbit

Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Sikadur-32 Normal Part B



Version **Revision Date:** SDS Number: Date of last issue: 2022/02/17 2024/02/22 100000007160 Date of first issue: 2017/09/08 5.0

Reproductive toxicity - As-

No toxicity to reproduction, No effects on or via lactation

sessment

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Section 12: Ecological information

Ecotoxicity

Components:

benzyl alcohol:

Toxicity to fish LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

ma/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

3,6-diazaoctanethylenediamin:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

100 mg/l

Exposure time: 72 h

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other :

LC50 (Daphnia magna (Water flea)): 0.167 mg/l

aquatic invertebrates Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic EC50 (Scenedesmus capricornutum (fresh water algae)): > 10

plants - 100 mg/l

Exposure time: 72 h

Adduct IA (epoxy amine adduct):

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): 3.13 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

LC50 (Danio rerio (zebra fish)): 1.62 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC50 (Daphnia magna (Water flea)): 1.75 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Section 14: Transport information

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : UN 1759

Proper shipping name : Corrosive solid, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Class : 8 Packing group : III

Labels : Corrosive

Packing instruction (cargo

aircraft)

Packing instruction (passen-

860

864

ger aircraft)

IMDG-Code

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no
Remarks : Alkalis

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
Hazchem Code : 2X
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002660

Tolerable Exposure Limits (TEL)

Not applicable

Sikadur-32 Normal Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/02/17

 5.0
 2024/02/22
 100000007160
 Date of first issue: 2017/09/08

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2024/02/22 Date format : dd.mm.yyyy

Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Sikadur-32 Normal Part B



Version 5.0

Revision Date: 2024/02/22

SDS Number: 100000007160

Date of last issue: 2022/02/17 Date of first issue: 2017/09/08

Changes as compared to previous version!

NZ / EN