

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

### Section 1: Identification

Product name : Sika MultiPrimer Marine

Product code : 000000035557

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

### Section 2: Hazard identification

#### GHS Classification

Flammable Liquids : 3.1B

Acute toxicity (Oral) : 6.1E

Acute toxicity (Inhalation) : 6.1E

Skin irritation : 6.3B

Eye irritation : 6.4A

Skin sensitisation : 6.5B

Toxic to Reproduction : 6.8A

Specific Target Organ Toxicity (Inhalation) : 6.9B

Aquatic toxicity (Acute or Chronic) : 9.1C

#### GHS label elements

Hazard pictograms :



# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

- Signal word : Danger
- Hazard statements : H225 Highly flammable liquid and vapour.  
H303 May be harmful if swallowed.  
H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H333 May be harmful if inhaled.  
H360FD May damage fertility. May damage the unborn child.  
H371 May cause damage to organs if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.
- Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P312 IF INHALED: Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ at-

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

tention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 50 -< 70
xylene	1330-20-7	>= 2.5 -< 10
dibutyltin dilaurate	77-58-7	>= 0.25 -< 1

## Section 4: First-aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Excessive lachrymation  
Loss of balance  
Vertigo

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

See Section 11 for more detailed information on health effects and symptoms.  
May be harmful if swallowed or if inhaled.  
Causes mild skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May damage fertility. May damage the unborn child.  
May cause damage to organs if inhaled.  
May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

---

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : 3YE

---

### Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

### Section 7: Handling and storage

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	WES-TWA	200 ppm 720 mg/m <sup>3</sup>	NZ OEL
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m <sup>3</sup>	NZ OEL

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhip-	Urine	End of	1.5 g/l	NZ BEI

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

		puric acid		shift		
--	--	------------	--	-------	--	--

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : colourless
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : > 70 °C (158 °F)
- Flash point : ca. -4 °C (25 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Not applicable
- Upper explosion limit / Upper flammability limit : 7 %(V)

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

---

Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	99.9915 hPa
Relative vapour density	:	No data available
Density	:	ca. 0.98 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	427 °C 427 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 10 - 20 mPa.s (20 °C (68 °F))
Viscosity, kinematic	:	< 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 66.61% w/w

---

### Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Peroxides Strong acids and oxidizing agents Bases

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

---

### Section 11: Toxicological information

#### Acute toxicity

May be harmful if swallowed or if inhaled.

#### Components:

##### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

##### **dibutyltin dilaurate:**

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

#### **Skin corrosion/irritation**

Causes mild skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

#### **Chronic toxicity**

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

May damage fertility. May damage the unborn child.

##### **STOT - single exposure**

May cause damage to organs if inhaled.



# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

Not classified based on available information.

## Section 12: Ecological information

### Ecotoxicity

#### Components:

##### **xylene:**

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia (water flea)): 1.17 mg/l  
Exposure time: 7 d

##### **dibutyltin dilaurate:**

Toxicity to fish : LC50 (Fish): 3.1 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

---

### Section 13: Disposal considerations

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.
- 

### Section 14: Transport information

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

- UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

- UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3
-

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

Hazchem Code : 3YE

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### HSNO Approval Number

HSR002662

### HSW Controls

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

## Section 16: Other information

### Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

# SAFETY DATA SHEET

## Sika MultiPrimer Marine



Version  
5.0

Revision Date:  
2022/05/24

SDS Number:  
000000035557

Date of last issue: 2021/08/09  
Date of first issue: 2017/11/15

---

OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN