Sika® Aktivator PRO



Version **Revision Date:** SDS Number: Date of last issue: 2021/04/14 2023/05/08 000000125402 Date of first issue: 2018/10/03 5.0

Section 1: Identification

Product name Sika® Aktivator PRO

Manufacturer or supplier's details

Sika (NZ) Ltd. Company

85-91 Patiki Road

Avondale

Auckland AKL 1026

+64 9 820 2900 Telephone

Emergency telephone number : 0800 734 607

E-mail address info@nz.sika.com

Telefax +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

Section 2: Hazard identification

GHS Classification

Flammable liquids Category 2

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 1

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

Aspiration hazard Category 1

Hazardous to the aquatic

environment - chronic hazard

Category 2

GHS label elements

Hazard pictograms











Signal word Danger

H225 Highly flammable liquid and vapour. Hazard statements

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Sika® Aktivator PRO



Revision Date: SDS Number: Version Date of last issue: 2021/04/14 000000125402 2023/05/08 Date of first issue: 2018/10/03 5.0

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light; Low	64742-49-0	>= 90 -<= 100
boiling point hydrogen treated naphtha		
bis(trimethoxysilylpropyl)amine	82985-35-1	>= 3 -< 10
3-trimethoxysilylpropane-1-thiol	4420-74-0	>= 0.25 -< 1

Section 4: First-aid measures

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

Small amounts splashed into eyes can cause irreversible tis-In case of eye contact

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Risk of serious damage to the lungs (by aspiration).

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

irritant effects

delayed

Aspiration may cause pulmonary oedema and pneumonitis.

Excessive lachrymation

Dermatitis Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

May be fatal if swallowed and enters airways.

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

Causes skin irritation.

Causes serious eye damage. May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

High volume water jet

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 3YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition.

Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Section 7: Handling and storage

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0	WES-TWA	300 ppm 890 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
		exposure)	Concentiation	

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

methanol	67-56-1	WES-STEL	250 ppm 328 mg/m3	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption			
		WES-TWA	200 ppm 262 mg/m3	NZ OEL

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

: No data available

Boiling point/boiling range : $> 70 \, ^{\circ}\text{C} \, (158 \, ^{\circ}\text{F})$

Flash point : ca. -4 °C (25 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower

flammability limit

0.6 %(V)

Vapour pressure : 60 hPa

Relative vapour density : No data available

Density : ca. 0.7 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 2 mPa.s (20 °C (68 °F))

Viscosity, kinematic : $< 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

696.3 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

methanol

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

bis(trimethoxysilylpropyl)amine:

Acute oral toxicity : LD50 Oral (Rat): 3,780 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 11,865 mg/kg

3-trimethoxysilylpropane-1-thiol:

Acute oral toxicity : LD50 Oral (Rat): 1,701 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,583 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Sika® Aktivator PRO



Revision Date: SDS Number: Version Date of last issue: 2021/04/14 2023/05/08 000000125402 Date of first issue: 2018/10/03 5.0

Section 12: Ecological information

Ecotoxicity

Components:

bis(trimethoxysilylpropyl)amine:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

NOEC (Oncorhynchus mykiss (rainbow trout)): 100 mg/l

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

3-trimethoxysilylpropane-1-thiol:

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 12.3 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 6.7 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 353

ger aircraft)

IMDG-Code

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

(n-heptane)

364

Class : 3
Packing group : II
Labels : 3

EmS Code : F-E, <u>S-E</u> Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Hazchem Code : 3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

10 / 12

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

HSNO Approval Number

HSR002662

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2023/05/08 Date format : dd.mm.yyyy

Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Sika® Aktivator PRO



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/14

 5.0
 2023/05/08
 000000125402
 Date of first issue: 2018/10/03

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN