

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Section 1: Identification

Product name : Sika BlackSeal Elastic

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Bituminous coating

Section 2: Hazard identification

GHS Classification

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements :

Prevention:

P261 Avoid breathing mist or vapours.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
10000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Asphalt	8052-42-4	>= 30 -< 50
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5	>= 0.1 -< 0.25

Section 4: First-aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No known significant effects or hazards.
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
- Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing method : Standard procedure for chemical fires.

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

ods

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : For personal protection see section 8.

Environmental precautions : No special environmental precautions required.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
No special handling advice required.
Follow standard hygiene measures when handling chemical products

Hygiene measures : When using do not eat or drink.
When using do not smoke.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

Materials to avoid : No special restrictions on storage with other products.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Asphalt	8052-42-4	WES-TWA (Fumes)	5 mg/m ³	NZ OEL

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
The filter class for the respirator must be suitable for the max-

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : liquid
paste
- Colour : brown
- Odour : slight
- Odour Threshold : No data available
- pH : ca. 11 (20 °C (68 °F))
- Melting point/freezing point : ≥ 0 °C (32 °F)
- Boiling point/boiling range : ca. 100 °C (212 °F)
- Flash point : > 232 °C (450 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : < 0.75 mmHg (180 °C (356 °F))
- Relative vapour density : No data available
- Density : ca. 1.03 g/cm³ (20 °C (68 °F))

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Solubility(ies)		
Water solubility	:	dispersible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	22,500 mPa.s (ca. 25 °C (77 °F))
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	no VOC contained

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity	:	LD50 Oral (Rat): 597 mg/kg
Acute inhalation toxicity	:	LC50: 0.4 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

Section 13: Disposal considerations

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

Hazchem Code : Not applicable

Special precautions for user

Not applicable

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002544 Construction Products Subsidiary Hazard Group Standard

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2022/10/20
Date format : dd.mm.yyyy

Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average
ADG : Australian Dangerous Goods Code.
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic

SAFETY DATA SHEET

Sika BlackSeal Elastic



Version
5.0

Revision Date:
2022/10/20

SDS Number:
100000021410

Date of last issue: 2020/07/26
Date of first issue: 2018/08/19

PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

NZ / EN