

PRODUCT DATA SHEET

Sika® Tite Undertile

FLEXIBLE, ONE PART, WATERBASED WATERPROOFING FOR USE UNDER FINISHES

DESCRIPTION

Sika® Tite Undertile is a highly flexible, fast-drying, Styrene Butadiene Rubber latex modified waterproofing membrane. Sika® Tite Undertile has excellent adhesion to most common building substrates and is suitable for internal and external waterproofing of shower recesses, bathrooms, balconies, roofs and decks.

USES

- Concrete
- Sand / cement screeds
- Cement render
- Fibrous cement sheeting
- Structural particle board sheeting
- Compressed fibrous cement sheeting
- Water resistant platerboard
- Structural plywood sheeting

CHARACTERISTICS / ADVANTAGES

- High Extensibility >300%
- Micro fibre enhanced reinforcement (Grey)
- Internal and external covered applications
- One part – No mixing, ready to use
- Water based - Low VOC's, Non hazardous
- Compatible with Sika® range of tile adhesives

PRODUCT INFORMATION

Packaging	15 Litre plastic pails
Shelf Life	12 months from date of manufacture in original, sealed containers, if the storage conditions are met.
Storage Conditions	Store in dry, weatherproof environment, protected from direct sunlight at temperatures between +5°C and +25°C
Colour	Grey
Consumption	FLOORS: Apply two coats to achieve a minimum dry film thickness of 1.0mm. Application coverage rate of 1L/m ² per coat. WALLS: Apply two coats to achieve a minimum dry film thickness of 0.5mm. Application coverage rate of 0.5L/m ² per coat. Coverage may vary depending on substrate and application method.
Curing Time	Allow a minimum of 12 hours curing prior to applying finished covering, and a minimum of 72 hours to cure before flood testing. Allow longer in adverse weather conditions.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

- Safety Data Sheet (SDS)

LIMITATIONS

LIMITATIONS

- Sika® Tite Undertile is not suitable for negative hydrostatic head of water pressure.
- Sika® Tite Undertile must not be applied over damp or wet substrates
- Sika® Tite Undertile must not be applied in rain or if bad weather is imminent.
- Sika® Tite Undertile must not be applied over coatings or contaminations.
- Sika® Tite Undertile must be applied at the recommended coverage rate.
- Sika® Tite Undertile must not be used in submerged applications.
- Sika® Tite Undertile must not be used as a trafficable, exposed or UV stable coating.
- Do not apply Sika® Tite Undertile when the temperature is below 10°C or greater than 35°C.
- Do not allow Sika® Tite Undertile to freeze.
- To eliminate contamination or damage, the finished covering must be applied as soon as Sika® Tite Undertile has cured.
- Timber floors must be overlaid with suitable cement sheeting prior to waterproofing.
- Contact Sika® Technical Services for advice if further information is required.

ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces to be waterproofed must be firm, clean, dry, structurally sound and smooth. All grease, oil, wax, curing compounds, dust, loose material, laitance and other contaminants must be removed. All projections and rough spots should be dressed off to achieve a level surface. The substrate surface must be continuous and not pond water.

Concrete

Allow at least 28 days for the concrete to cure. Concrete should be left with an open surface – standard wood float or broom finish. All traces of curing compounds or sealers should be removed prior to application. Old concrete must be thoroughly cleaned and washed and allowed to dry. The surface should be even unless falls are incorporated where required, imperfections to be repaired with a suitable Sika® Mono-

Top repair mortar.

Sand / Cement Screeds and Renders

The screeds and / or renders must conform to the appropriate standard and should be left with a wood float finish and left to cure for at least cure for 7 days.

Building Boards

Water resistant plasterboard, fibrous cement sheeting, marine ply must be solidly fixed in accordance with the manufacturer's instructions specifically for tiling. The area must be primed with ECO SYSTEMS® Eco Prime WB, particularly where a jointing compound has been used.

Particleboard

Particleboard must be fixed in accordance with the manufacturer's instructions specifically for tiling and free from any movement. Secure floor with additional fixings and wedges, sand any surface contamination after initial preparation. The area must be primed with ECO SYSTEMS® Prep 'N' Prime.

Existing Tiles

Any existing tiles must be well bonded and be free from any sealers or coatings. It may be necessary to mechanically prepare the area. Dense, low absorbent surfaces must be primed with ECO SYSTEMS® Prep 'N' Prime.

Joint Treatment

Sika® SealTape is a reinforcement tape with a woven bonding mesh and an expansion zone the middle to be used to reinforce all changes of direction. It comes as performed corners, wall flashings, floor flashings and rolls. It is 0.6 mm thick and coloured yellow.

TILING

Sika® Tite Undertile is compatible with a range of Sika® polymer modified tile adhesives, Contact Sika Technical Service for further advice.

CLEANING OF TOOLS

Clean tools and equipment with clean water while the material is still wet. Cured coating can only be removed mechanically.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The

user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited
85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz



Product Data Sheet
Sika® Tite Undertile
October 2023, Version 01.02
021790202200000012

SikaTiteUndertile-en-NZ-(10-2023)-1-2.pdf

