

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

---

### Section 1: Identification

Product name : Sika® Primer-206 G+P

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent, Product is not intended for consumer use

---

### Section 2: Hazard identification

#### GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irritation : Category 2

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure : Category 2

#### GHS label elements

Hazard pictograms :



Signal word : Danger

---

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

---

Hazard statements : H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
P284 Wear respiratory protection.

### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### **Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 50 -< 70
Hexamethylene diisocyanate, oligomers	28182-81-2	>= 1 -< 10
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	>= 1 -< 10
Isophorondiisocyanate homopolymer	53880-05-0	>= 1 -< 10
n-butyl acetate	123-86-4	>= 1 -< 10
2-methoxy-1-methylethyl acetate	108-65-6	>= 1 -< 10
xylene	1330-20-7	>= 0.1 -< 1
ethylbenzene	100-41-4	>= 0.1 -< 1
hexamethylene-di-isocyanate	822-06-0	>= 0.1 -< 1

## Section 4: First-aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and : irritant effects  
sensitising effects

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

delayed

Allergic reactions  
Excessive lachrymation  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

---

### Section 5: Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use water spray to cool unopened containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 3YE

---

### Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for : Contain spillage, and then collect with non-combustible ab-

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

containment and cleaning up sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### Section 7: Handling and storage

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

ethyl acetate	141-78-6	WES-TWA	200 ppm 720 mg/m3	NZ OEL
Hexamethylene diisocyanate, oligomers	28182-81-2	WES-TWA	0.02 mg/m3 (NCO)	NZ OEL
Further information: Skin sensitiser, Respiratory sensitiser				
		WES-STEEL	0.07 mg/m3 (NCO)	NZ OEL
		WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m3 (NCO)	NZ OEL
		WES-STEEL (Inhalable Fraction and Vapour)	0.07 mg/m3 (NCO)	NZ OEL
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m3 (NCO)	NZ OEL
Further information: Skin sensitiser, Respiratory sensitiser				
		WES-STEEL (Inhalable Fraction and Vapour)	0.07 mg/m3 (NCO)	NZ OEL
n-butyl acetate	123-86-4	WES-TWA	150 ppm 713 mg/m3	NZ OEL
		WES-STEEL	200 ppm 950 mg/m3	NZ OEL
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
Further information: Ototoxin				
ethylbenzene	100-41-4	WES-STEEL	40 ppm 176 mg/m3	NZ OEL
Further information: Ototoxin, Skin absorption				
		WES-TWA	20 ppm 88 mg/m3	NZ OEL
hexamethylene-di-isocyanate	822-06-0	WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m3 (NCO)	NZ OEL
Further information: Skin sensitiser, Respiratory sensitiser				
		WES-STEEL (Inhalable Fraction and Vapour)	0.07 mg/m3 (NCO)	NZ OEL

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
ethylbenzene	100-41-4	Sum of	Urine	End of	0.25 g/g cre-	NZ BEI

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

		mandelic acid and phenylglyoxylic acids		exposure or end of shift	atinine	
hexamethylene-diisocyanate	822-06-0	1,6-Hexamethylene diamine	Urine	End of shift	15 µg/g creatinine	ACGIH BEI

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : black
- Odour : ester-like
- Odour Threshold : No data available
- pH : ca. 7  
Concentration: 50 %
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : > 77 °C (> 171 °F)
- Flash point : -4 °C (25 °F)  
(Method: closed cup)
- Evaporation rate : No data available

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

---

Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	11.5 %(V)
Lower explosion limit / Lower flammability limit	:	2.1 %(V)
Vapour pressure	:	99.9915 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.02 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	333 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 10 mPa.s (20 °C (68 °F))
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	619 g/l

---

### Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.  Avoid moisture.
Incompatible materials	:	Strong acids and strong bases Oxidizing agents

---



# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

Peroxides

### Section 11: Toxicological information

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **ethyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **Hexamethylene diisocyanate, oligomers:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

##### **tris(p-isocyanatophenyl) thiophosphate:**

- Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg  
Remarks: see user defined free text
- Acute inhalation toxicity : LC50 (Rat): 5.721 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **n-butyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **2-methoxy-1-methylethyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **xylene:**

- Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### **ethylbenzene:**

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg  
**hexamethylene-di-isocyanate:**  
Acute oral toxicity : LD50 Oral (Rat): 746 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0.124 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

### Skin corrosion/irritation

Not classified due to lack of data.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Chronic toxicity

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

#### STOT - single exposure

Not classified due to lack of data.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Remarks : Toxicology data for the components  
Information given is based on data on the components and  
the toxicology of similar products.  
Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

---

### Section 12: Ecological information

#### Ecotoxicity

##### Components:

##### **Hexamethylene diisocyanate, oligomers:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **n-butyl acetate:**

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l  
plants Exposure time: 72 h

##### **xylene:**

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
icity) Exposure time: 56 d

Toxicity to daphnia and other : NOEC (Daphnia (water flea)): 1.17 mg/l  
aquatic invertebrates (Chron- Exposure time: 7 d  
ic toxicity)

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

##### Product:

Additional ecological infor- : There is no data available for this product.  
mation

---

### Section 13: Disposal considerations

#### **Disposal methods**

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

Do not re-use empty containers.

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

Do not burn, or use a cutting torch on, the empty drum.

### Section 14: Transport information

#### International Regulations

Marine pollutant : no

#### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

#### IMDG-Code

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Hazchem Code : 3YE  
Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### Section 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

### HSNO Approval Number

HSR002669

### HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

## Section 16: Other information

Revision Date : 2023/08/09  
Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NZ BEI : New Zealand. Biological Exposure Indices  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

# SAFETY DATA SHEET

## Sika® Primer-206 G+P



Version  
5.0

Revision Date:  
2023/08/09

SDS Number:  
000000020203

Date of last issue: 2022/11/03  
Date of first issue: 2017/12/19

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

NZ / EN