Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
Section 1:	: Identification			
Product name		:	Sikafloor-91/94 Part A	
Manu	facturer or supplier's d	letai	ils	
Comp	bany	:	Sika (NZ) Ltd. 85-91 Patiki Road Avondale Auckland AKL 1026	
Telep	hone	:	+64 9 820 2900	
Emergency telephone number		• :	0800 734 607	
E-mai	il address	:	info@nz.sika.com	
Telefax		:	+64 9 828 4091	

Section 2: Hazard identification

GHS Classification Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 2
Skin sensitisation	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 2
GHS label elements Hazard pictograms	:	!
Signal word	:	Warning
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02	SDS Number: 100000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14			
		P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection.				
		Response:				
		for several minutes. Removeasy to do. Continue rinsin P333 + P313 If skin irritatio vice/ attention. P337 + P313 If eye irritatio tention.	EYES: Rinse cautiously with water ve contact lenses, if present and			
		Disposal:				
		P501 Dispose of contents/ disposal plant.	container to an approved waste			

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 70 -< 90
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 -< 10
bis(isopropyl)naphthalene	38640-62-9	>= 2.5 -< 10

Section 4: First-aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	:	Immediately flush eye(s) with plenty of water.	
		2/10	

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14	
			Remove contact lenses. Keep eye wide open while rinsin If eye irritation persists, consult a		
If swallowed		:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.		
Most important symptoms and effects, both acute and delayed		:	irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed and symptoms. Causes skin irritation. May cause an allergic skin react Causes serious eye irritation.		
Notes	to physician	:	Treat symptomatically.		

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Hazchem Code	:	3Z

Section 6: Accidental release measures

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

Sikafloor-91/94 Part A



Versio 4.0	on Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
		r	espective authorities.	
	Methods and materials for containment and cleaning up	6	Soak up with inert absorbent mate acid binder, universal binder, saw Keep in suitable, closed container	dust).
Sect	ion 7: Handling and storage	•		
	Advice on protection against fire and explosion	: 1	Normal measures for preventive f	ire protection.
	Advice on safe handling	s E F F r r t S F F	Avoid exceeding the given occupa section 8). Do not get in eyes, on skin, or on For personal protection see section Persons with a history of skin sen na, allergies, chronic or recurrent not be employed in any process in used. Smoking, eating and drinking sho plication area. Follow standard hygiene measure products	clothing. on 8. sitisation problems or asth- t respiratory disease should n which this mixture is being uld be prohibited in the ap-
	Hygiene measures	V V V	Handle in accordance with good i practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and a	
	Conditions for safe storage	k (Keep container tightly closed in a place. Containers which are opened must rept upright to prevent leakage. Store in accordance with local reg	st be carefully resealed and

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration
	(gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self-
	contained breathing apparatus must be used.

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
Hand	protection	:	Chemical-resistant, impervious approved standard should be chemical products if a risk ass essary.	worn at all times when handling
Eye protection		:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.	
Skin a	nd body protection	:	<i>2</i> 1	ation to its type, to the concen- us substances, and to the spe-

Section 9: Physical and chemical properties

Appearance	:	liquid
Colour	:	clear, cloudy
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 100 °C (> 212 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.01 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.12 g/cm3 (20 °C (68 °F))
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available

Sikafloor-91/94 Part A



Vers 4.0	ion Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	No data available	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic	:	3,000 mPa.s (20 °C (68 °F))	
	Viscosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	
	Volatile organic compounds (VOC) content	:	0.5 g/l	

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

<u>Components:</u> reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):					
Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg			
bis(isopropyl)naphthalene: Acute oral toxicity	:	LD50 Oral (Rat): > 3,900 mg/kg			
Acute inhalation toxicity	:	LC50 (Rat): > 5.64 mg/l Exposure time: 4 h Test atmosphere: dust/mist			
Acute dermal toxicity	:	LD50 Dermal (Rat): > 4,500 mg/kg			

Sikafloor-91/94 Part A



ersion .0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14				
Skin d	corrosion/irritation							
Cause	es skin irritation.							
	Serious eye damage/eye irritation Causes serious eye irritation.							
Respi	Respiratory or skin sensitisation							
	Skin sensitisation May cause an allergic skin reaction. Respiratory sensitisation Not classified based on available information.							
-								
Chror	nic toxicity							
	cell mutagenicity assified based on availal	ble in	formation.					
	Carcinogenicity Not classified based on available information. Reproductive toxicity Not classified based on available information. STOT - single exposure Not classified based on available information.							
-								
	STOT - repeated exposure Not classified based on available information.							
Aspiration toxicity Not classified based on available information.								
Section 12	2: Ecological information	on						
Ecoto	oxicity							
	oonents:							
	on product: bisphenol- nt ≤ 700):	-A-(e	pichlorhydrin); epoxy re	sin (number average molecular				
	ty to fish		.C50 (Oncorhynchus myki Exposure time: 96 h	ss (rainbow trout)): 2 mg/l				
	ty to daphnia and other ic invertebrates		C50 (Daphnia magna (W Exposure time: 48 h	ater flea)): 1.8 mg/l				
	stence and degradabilititation taken the state of the sta	ty						
	cumulative potential ta available							

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
Mob	bility in soil			
No c	lata available			
Othe	er adverse effects			
Proc	duct:			
Add mati	itional ecological infor- on	:	Toxic to aquatic life with lor	g lasting effects.
Section	13: Disposal considerat	ions	3	
Disp	oosal methods			
Was	te from residues	:	courses or the soil.	allowed to enter drains, water waterways or ditches with chemi- anagement company.
Con	taminated packaging	:	Empty remaining contents. Dispose of as unused produ Do not re-use empty contai	

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s.
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	964
Packing instruction (passen- ger aircraft)	:	964
IMDG-Code		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	no
	Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft) IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code	Proper shipping name:Class:Packing group:Labels:Packing instruction (cargo:aircraft):Packing instruction (passen- ger aircraft):IMDG-Code:UN number:Proper shipping name:Class:Packing group:Labels:EmS Code:

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02		SDS Number: 10000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
UN nu	Imber	:	UN 3082	
Prope	r shipping name	:	ENVIRONMENTALLY HA	ZARDOUS SUBSTANCE, LIQUID,
Class		:	9	
Packir	ng group	:	III	
Labels	3	:	9	
Hazch	em Code	:	3Z	

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002670

HSW Controls

Certified handler certificate not required. Tracking hazardous substance not required. Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC

: On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date Date format	:	2023/06/02 dd.mm.yyyy
Full text of other abbreviation	ons	
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in

Sikafloor-91/94 Part A



Version 4.0	Revision Date: 2023/06/02	SDS Number: 100000008588	Date of last issue: 2022/04/28 Date of first issue: 2017/06/14
MARP OEL PBT PNEC REAC SVHC	Н	 period) International Convention Ships, 1973 as modified Occupational Exposure Persistent, bioaccumula Predicted no effect cond Regulation (EC) No 190 and of the Council of 18 istration, Evaluation, Au 	ative and toxic centration 07/2006 of the European Parliament 9 December 2006 concerning the Reg- thorisation and Restriction of Chemi- ning a European Chemicals Agency
vPvB		: Very persistent and very	y bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NZ / EN