

PRODUCT DATA SHEET

S-Leafguard round

PREFABRICATED POLYPROPYLENE LEAFGUARD



DESCRIPTION

S-Leafguard round is a prefabricated Polypropylene (PP) basket with fixing wing nut

USES

This product may only be used by experienced professionals.

The S-Leafguard round is used as a gravel and leaf protection for Sarnafil® S-Drains PVC in flat roofs.

CHARACTERISTICS / ADVANTAGES

- Resistant to UV exposure
- Ease of application



PRODUCT INFORMATION

| Packaging | Depending on the order quantity and product size, the products are packaged on pallets or in cartons | | |
|---------------------|---|-----------------|----------------------|
| Appearance / Colour | Surface Colour | smooth black | |
| Shelf Life | 5 years from date of production. | | |
| Storage Conditions | The products must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging. | | |
| Dimensions | Basket outside diamet- er | Basket height | Suitable for |
| | 237 mm | 82 mm | S-Drain PVC 56 – 160 |

SYSTEM INFORMATION

| System Structure | The following products must be considered for use depending on roof |
|------------------|---|
| | design: S-Drain PVC 56 - 160 |
| | |

Product Data Sheet S-Leafguard round August 2019, Version 01.01 020945051450000004

APPLICATION INFORMATION

| Ambient Air Temperature | -20 °C min. / +60 °C max. |
|-------------------------|---------------------------|
| Substrate Temperature | -30 °C min. / +60 °C max. |

APPLICATION INSTRUCTIONS

APPLICATION

Refer to the relevant section in the Installation instructions: Sarnafil® and Sikaplan® flat roof systems

FURTHER DOCUMENTS

Installation instructions: Sarnafil® and Sikaplan® flat roof systems

LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of S-Leafguard round is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Sika (NZ) Limited

85-91 Patiki Road Avondale, Auckland 1026 New Zealand 0800 745 269 www.sika.co.nz





Product Data Sheet S-Leafguard round August 2019, Version 01.01 020945051450000004

ECOLOGY HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet.Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

BUILDING TRUST

S-Leafguardround-en-NZ-(08-2019)-1-1.pdf

