# Sikadur-31 SBA S04 (A)



Version Date of last issue: 2022/06/12 **Revision Date:** SDS Number: 2024/12/11 100000029865 Date of first issue: 2020/06/17 2.0

#### **Section 1: Identification**

Product name Sikadur-31 SBA S04 (A)

## Manufacturer or supplier's details

Company Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone +64 9 820 2900

Emergency telephone number: 0800 734 607

E-mail address info@nz.sika.com

Telefax +64 9 828 4091

## Recommended use of the chemical and restrictions on use

Product use : Adhesive

### Section 2: Hazard identification

**GHS Classification** 

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation Category 1

Carcinogenicity (Inhalation) Category 1

Carcinogenicity Category 2

Specific target organ toxicity - :

repeated exposure (Inhala-

tion)

Category 2 (Lungs)

Hazardous to the aquatic

environment - chronic hazard

Category 3

**GHS** label elements

Hazard pictograms







# Sikadur-31 SBA S04 (A)



Version Revision Date: SDS Number: Date of last issue: 2022/06/12 2024/12/11 100000029865 Date of first issue: 2020/06/17 2.0

Signal word Danger

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H350 May cause cancer by inhalation. H351 Suspected of causing cancer.

H373 May cause damage to organs (Lungs) through prolonged

or repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

## Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

#### Storage:

P405 Store locked up.

## Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

### Other hazards which do not result in classification

None known.

#### Section 3: Composition/information on ingredients

Substance / Mixture Mixture

Components

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 50 -< 70
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 10 -< 20
calcium carbonate	471-34-1	>= 1 -< 10
Quartz (SiO2) <5µm	14808-60-7	>= 1 -< 10
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8	>= 3 -< 10
Hydrocarbons, C10-C13, aromatic, >1% Naph-thalene	64742-94-5	>= 0.25 -< 1
naphthalene	91-20-3	>= 0.1 -< 0.25

#### Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects Allergic reactions

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.
May cause cancer by inhalation.
Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

exposure if inhaled.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

ng meth- : Standard procedure for chemical fires.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 2Z

Section 6: Accidental release measures

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

## Section 8: Exposure controls/personal protection

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
Quartz (SiO2)	14808-60-7	WES-TWA (Respirable dust)	0.05 mg/m3	NZ OEL	
	Further information: Confirmed carcinogen				
		WES-TWA (Respirable dust)	0.025 mg/m3	NZ OEL	
calcium carbonate	471-34-1	WES-TWA	10 mg/m3 (Calcium car- bonate)	NZ OEL	
Quartz (SiO2) <5µm	14808-60-7	WES-TWA (Respirable dust)	0.05 mg/m3	NZ OEL	
	Further information: Confirmed carcinogen				
		WES-TWA (Respirable dust)	0.025 mg/m3	NZ OEL	
naphthalene	91-20-3	WES-STEL	2 ppm 10 mg/m3	NZ OEL	
	Further information: Suspected human carcinogen, Skin absorption				
		WES-TWA	0.5 ppm 2.6 mg/m3	NZ OEL	

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

## Section 9: Physical and chemical properties

Appearance : paste

Colour : off-white

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/ range / Freez-

ing point

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : ca. 2 g/cm3 (25 °C (77 °F))

Bulk density : Not applicable

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

2.2 g/l

## Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

## **Section 11: Toxicological information**

#### **Acute toxicity**

Not classified based on available information.

## **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

1,4-bis(2,3 epoxypropoxy)butane:

Acute oral toxicity : LD50 Oral (Rat): 1,163 mg/kg

# Sikadur-31 SBA S04 (A)



Version **Revision Date:** SDS Number: Date of last issue: 2022/06/12 2024/12/11 100000029865 Date of first issue: 2020/06/17 2.0

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

Not classified based on available information.

## **Chronic toxicity**

#### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer by inhalation. Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

## **Aspiration toxicity**

Not classified based on available information.

#### Section 12: Ecological information

## **Ecotoxicity**

#### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

aquatic invertebrates

Exposure time: 48 h

naphthalene:

M-Factor (Acute aquatic tox-

M-Factor (Chronic aquatic

toxicity)

# Sikadur-31 SBA S04 (A)



Revision Date: Version SDS Number: Date of last issue: 2022/06/12 2024/12/11 100000029865 Date of first issue: 2020/06/17 2.0

#### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

## Section 13: Disposal considerations

**Disposal methods** 

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

## **Section 14: Transport information**

## **International Regulations**

IATA-DGR

UN/ID No. UN 3077

Proper shipping name Environmentally hazardous substance, solid, n.o.s., Environ-

mentally hazardous substance, solid, n.o.s.

Class 9 Packing group Ш

Miscellaneous Labels

Packing instruction (cargo

aircraft)

956

Packing instruction (passen-

ger aircraft)

956

Environmentally hazardous yes

**IMDG-Code** 

UN number UN 3077

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, Proper shipping name

N.O.S.

Class 9

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**NZS 5433** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
Hazchem Code : 2Z
Marine pollutant : yes

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **Section 15: Regulatory information**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

## **HSNO Approval Number**

HSR002679

#### **Tolerable Exposure Limits (TEL)**

Not applicable

## **Environmental Exposure Limits (EEL)**

Not applicable

#### **HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

#### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

#### **Section 16: Other information**

# Sikadur-31 SBA S04 (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/06/12

 2.0
 2024/12/11
 100000029865
 Date of first issue: 2020/06/17

Revision Date : 2024/12/11 Date format : dd.mm.yyyy

Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN