

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Section 1: Identification

Product name : Sikafloor-359 N Part A

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Polyurethane coating

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Serious eye damage/eye irritation : Category 2

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

Hazardous to the aquatic environment - chronic hazard : Category 3

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P284 Wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 2.5 -< 10
Polyacrylate	37237-99-3	>= 1 -< 10
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane-1,2-diylbiscarbamate	59719-67-4	>= 2.5 -< 10
ethylbenzene	100-41-4	>= 2.5 -< 10
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 0.25 -< 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0.1 -< 0.25
hexahydromethylphthalic anhydride	25550-51-0	>= 0.1 -< 1
dibutyltin dichloride	683-18-1	>= 0.025 -< 0.1

Section 4: First-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Allergic reactions
Excessive lachrymation
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of damaging fertility.
May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use water spray to cool unopened containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : •3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
------------	---------	------------------------	----------------------------------	-------

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

		exposure)	concentration	
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m ³	NZ OEL
Further information: Ototoxin				
ethylbenzene	100-41-4	WES-STEL	40 ppm 176 mg/m ³	NZ OEL
Further information: Ototoxin, Skin absorption				
		WES-TWA	20 ppm 88 mg/m ³	NZ OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : various
- Odour : hydrocarbon-like
- Odour Threshold : No data available

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

pH	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 33 °C (91 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	7.9993 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.7 g/cm ³ (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	ca. 431 °C (808 °F)
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	221.6 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

hexahydromethylphthalic anhydride:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

dibutyltin dichloride:

Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

xylene:

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia (water flea)): 1.17 mg/l
Exposure time: 7 d

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 87.1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 18.6 mg/l
Exposure time: 72 h

dibutyltin dichloride:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1.4 mg/l
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

No data available

Bioaccumulative potential

No data available

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

National Regulations

NZS 5433

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002662

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2023/02/19
Date format : dd.mm.yyyy

Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit
ADG : Australian Dangerous Goods Code.
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

SAFETY DATA SHEET

Sikafloor-359 N Part A



Version
5.0

Revision Date:
2023/02/19

SDS Number:
000000122200

Date of last issue: 2021/04/15
Date of first issue: 2017/12/19

IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN