

Sika[®] Deckweb

Polypropylene Fabric Reinforcement

Positioning

Description

Sika[®] Deckweb is a spun bond polypropylene matting fabric, used to reinforce Sika waterproofing membranes, resins and coatings.

Use

As a reinforcing fabric in various liquid applied products.

Advantages

- Excellent wetting ability
- Easily conforms to complex shapes.
- Excellent wet and dry strength
- Non-wrinkle or creasing
- High grab tensile strength
- No process wax or odour

Product Data

Form:

Spun bond polypropylene matting fabric

Colour:

White

Roll size:

190mm wide x 50m long

Storage & Shelf Life:

24 months when stored in unopened original packaging in cool dry conditions between 5°C and 30°C. Protect from frost and exposure to direct sunlight.

Packaging:

Technical Data

Weight

50 g/m²

Grab tensile strength:

9.0 kN/m (Cross direction)

Elongation at break:

41% (Machine direction)

Pore Size:

110 microns

Application Conditions

Specification

All work is to be carried out in accordance with the appropriate Sika (NZ) Ltd product specifications and details.

Application method

- Immediately after the application of the Sika membrane/resin/coating, apply Sika[®] Deckweb directly onto the liquid material, as detailed in the appropriate specification.

Notes

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.



Health & Safety Instructions

Protective Measures

- To avoid rare allergic reactions, we recommend the use of protective gloves. Change soiled work clothes and wash hands before breaks and after finishing work.
- Local regulations as well as health and safety advice on packaging labels must be observed.
- For further information refer to the Sika Material Safety Data Sheet which is available on request.
- If in doubt always follow the directions given on the pack or label.

Important Notes

- Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities.
- Detailed health and safety information as well as detailed precautionary measures e.g. physical, toxicological and ecological data can be obtained from the safety data sheet.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika (NZ) Ltd
PO Box 19192
Avondale
Auckland
New Zealand

Phone: 0800 SIKA NZ
Fax: 0800 SIKA FAX
Email: info@nz.sika.com

0800 745 269
0800 745 232
www.sika.co.nz

