

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

Section 1: Identification

Product name : SikaSeal Roof & Gutter clear

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Section 2: Hazard identification

GHS Classification

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Siloxanes and silicones, di-Me, hydroxy-terminated	70131-67-8	>= 50 -< 70
butan-2-one O,O',O''-(methylsilylidyne)trioxime	22984-54-9	>= 1 -< 10
toluene	108-88-3	>= 0.1 -< 1
dibutyltin dilaurate	77-58-7	>= 0.1 -< 0.25
butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	34206-40-1	>= 0.1 -< 1

Section 4: First-aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

- Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitising effects
Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
- Notes to physician : Treat symptomatically.
-

Section 5: Fire-fighting measures

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
-

Section 7: Handling and storage

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	WES-TWA	20 ppm 75 mg/m ³	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring, Skin absorption			
		WES-STEL	100 ppm 377 mg/m ³	NZ OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
toluene	108-88-3	Toluene	Urine	End of exposure or end of shift	0.03 mg/l	NZ BEI
		o-Cresol	Urine	End of exposure or end of shift	0.3 mg/g creatinine	NZ BEI

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : paste
- Colour : transparent
- Odour : slight
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 400 °C (> 752 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 0.01 hPa

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

Relative vapour density	:	No data available
Density	:	ca. 1.02 g/cm ³ (23 °C (73 °F))
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	3.0 g/l

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	butanone oxime

Section 11: Toxicological information

Acute toxicity

Not classified due to lack of data.

Components:

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Section 12: Ecological information

Ecotoxicity

Components:

dibutyltin dilaurate:

Toxicity to fish : LC50 (Fish): 3.1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

Section 13: Disposal considerations

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.

Section 14: Transport information

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : Not applicable

Proper shipping name : Not applicable

Class : Not applicable

Subsidiary risk : Not applicable

Packing group : Not applicable

Labels : Not applicable

Packing instruction (cargo aircraft) : Not applicable

Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable

Proper shipping name : Not applicable

Class : Not applicable

Subsidiary risk : Not applicable

Packing group : Not applicable

Labels : Not applicable

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version
1.0

Revision Date:
2024/05/22

SDS Number:
100000040185

Date of last issue: -
Date of first issue: 2024/05/22

EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable
Marine pollutant : no

Special precautions for user

Not applicable

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002670

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2024/05/22
Date format : dd.mm.yyyy

Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices

SAFETY DATA SHEET

SikaSeal Roof & Gutter clear



Version 1.0	Revision Date: 2024/05/22	SDS Number: 100000040185	Date of last issue: - Date of first issue: 2024/05/22
----------------	------------------------------	-----------------------------	--

- NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

- NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average
- NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit
- ADG : Australian Dangerous Goods Code.
- ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

- CAS : Chemical Abstracts Service
- DNEL : Derived no-effect level
- EC50 : Half maximal effective concentration
- GHS : Globally Harmonized System
- IATA : International Air Transport Association
- IMDG : International Maritime Code for Dangerous Goods
- LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

- LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

- MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

- OEL : Occupational Exposure Limit
- PBT : Persistent, bioaccumulative and toxic
- PNEC : Predicted no effect concentration
- REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

- SVHC : Substances of Very High Concern
- vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NZ / EN