Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

Section 1: Identification

Product name : Sikafloor-80 EpoCem Primer Part A

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Special system

Section 2: Hazard identification

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2

Skin sensitisation : Category 1

Hazardous to the aquatic

environment - chronic hazard

Category 2

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : ,

Prevention:

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) | 25068-38-6 | >= 30 -< 50 |
| reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 9003-36-5 | >= 10 -< 20 |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 68609-97-2 | >= 1 -< 10 |

Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects Allergic reactions

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 3Z

Section 6: Accidental release measures

Personal precautions, protec- :

tive equipment and emer-

Use personal protective equipment.

Deny access to unprotected persons.

Sikafloor-80 EpoCem Primer Part A



Version **Revision Date:** SDS Number: Date of last issue: 2021/04/05 00000020266 Date of first issue: 2016/02/09 2022/09/08 6.0

gency procedures

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Section 9: Physical and chemical properties

Appearance : liquid

Colour : white

Odour : odourless

Odour Threshold : No data available

pH : ca. 8

Concentration: 100 %

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : > 100 °C (> 212 °F)

Flash point : $> 101 \, ^{\circ}\text{C} \, (> 214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : ca. 1.05 g/cm3 (20 °C (68 °F))

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

no VOC contained

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Sikafloor-80 EpoCem Primer Part A



Revision Date: Date of last issue: 2021/04/05 Version SDS Number: 2022/09/08 00000020266 Date of first issue: 2016/02/09 6.0

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

Class 9 Packing group Ш

Miscellaneous Labels

Packing instruction (cargo 964

aircraft)

Packing instruction (passen-

ger aircraft)

964

Remarks Transport in accordance with special regulation A 197

IMDG-Code UN 3082 **UN** number

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class 9 Packing group Ш Labels EmS Code F-A, S-F Marine pollutant

Transport in accordance with 2.10.2.7 of the IMDG-Code Remarks

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Sikafloor-80 EpoCem Primer Part A



SDS Number: Version Revision Date: Date of last issue: 2021/04/05 000000020266 Date of first issue: 2016/02/09 2022/09/08 6.0

National Regulations

NZS 5433

UN number UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name

N.O.S.

(epoxy resin)

Class 9 Packing group Ш Labels 9 Hazchem Code 3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002670

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Full text of other abbreviations

ADG Australian Dangerous Goods Code.

European Agreement concerning the International Carriage of **ADR**

Dangerous Goods by Road

CAS **Chemical Abstracts Service** Derived no-effect level DNEL

EC50 Half maximal effective concentration **GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

Sikafloor-80 EpoCem Primer Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/05

 6.0
 2022/09/08
 000000020266
 Date of first issue: 2016/02/09

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN