



SikaForce[®]-7260 Cleaner

Liquid for cleaning of tools and application equipment

Technical Product Data

Chemical base	Dipropylene glycol ether
Colour (CQP ¹ 001-1)	Transparent
Density ² (CQP 006-6)	0.96 g/cm ³ approx.
Viscosity ²	4 mPa·s approx.
Vapour pressure	25°C (75°F) 0.4 mm Hg approx.
Boiling point	190°C (375°F) approx.
Flash point	80°C (175°F) approx.
Shelf life (storage between 10 and 30°C in tightly closed packaging)	12 months

¹⁾ CQP = Corporate Quality Procedure

²⁾ 23°C (73°F) / 50% r.h.

Description

SikaForce[®]-7260 Cleaner is a high boiling liquid for removing of non-cured one and two component polyurethane products.

This product is manufactured in accordance with ISO 9001 / 14001 quality assurance systems and the responsible care program.

Product Benefits

- Not classified
- Neutralises the isocyanate groups in polyurethane products

Areas of Application

SikaForce[®]-7260 Cleaner is used for cleaning of tools and application equipment used for one and two component polyurethane products and for cleaning and flushing of one and two component application equipment.

This product is suitable for professional experienced users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

Directions for Use

Removal of one and two component polyurethane products should take place while they are still liquid. When using SikaForce®-7260 Cleaner at temperatures above 30°C, local extraction is recommended.

Clean contaminated parts/tools with SikaForce®-7260 Cleaner using a brush. If necessary immerse parts in SikaForce®-7260 Cleaner prior to the cleaning process.

For two component equipment, flushing with recirculation is recommended.

By mixing a lot of polyurethane with a small amount of SikaForce®-7260 Cleaner, the mixture may develop heat. Consequently, there should always be an excess of SikaForce®-7260 Cleaner.

Storage Conditions

SikaForce®-7260 Cleaner has to be kept in a tightly closed packaging and stored in a well-ventilated storage room.

Further Information

Copies of the following publications are available on request:

- Material Safety Data Sheet

Packaging Information

Drum	200 l
------	-------

Value Bases

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Health and Safety Information

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



The Sika logo, consisting of the word "Sika" in a stylized yellow font on a red triangular background, with a registered trademark symbol (®) to the right.

Sika (NZ) Limited
PO Box 19192, Auckland 1746, NZ.
0800 745 269 | www.sika.co.nz

Innovation & Consistency | since 1910