

## PRODUCT DATA SHEET

# Sarnafil® PVC Walkway Pad (CN)

INJECTION MOULDED PVC WALKWAY PAD

SIKA NZ  
APPROVED  
CONTRACTOR  
ONLY

## DESCRIPTION

Sarnafil® PVC Walkway Pad is made of high quality PVC by injection moulding procedure.

## USES

Sarnafil® PVC Walkway Pad is used to provide a durable, slip-resistant walkway for roof maintenance or access on any Sarnafil® PVC roofing system.

## CHARACTERISTICS / ADVANTAGES

- Resistant to permanent UV irradiation
- Outstanding slip resistant surface
- Hot air welding without use of open flames
- Rainwater drainage from beneath the Sarnafil® Walkway Pad PVC is provided by a network of moulded channels

## APPROVALS / STANDARDS

Quality management system EN ISO 9001/14001

## PRODUCT INFORMATION

Chemical Base	Polyvinyl chloride (PVC)
Packaging	20 pcs/box
Appearance / Colour	Grey
Shelf Life	Sarnafil® PVC Walkway Pad does not expire during correct storage.
Storage Conditions	Sarnafil® PVC Walkway Pad shall be stored in dry conditions.
Length	605±8 mm
Width	600±10 mm (exclude welding lap)
Thickness	7 mm (±0.2 mm) including 3 mm non-slip chevron pattern embossing

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	-20 °C min. / +60 °C max.
<b>Substrate Temperature</b>	-30 °C min. / +60 °C max.
<b>System Structure</b>	Compatible products: Sarnafil® PVC -types

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

### Geographical / Climate

The use of Sarnafil® PVC Walkway Pad is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

## ECOLOGY HEALTH AND SAFETY

### APPLICATION

Installation works must be carried out only by Sika instructed contractors for roofing. Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets. Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

### APPLICATION METHOD / TOOLS

According to the valid installation instructions for Sarnafil®. Sarnafil® PVC Walkway Pad is installed on site by hot air welding the welding tabs directly onto the Sarnafil® G/S membrane.

- Mark a line (e.g. chalk line) in the direction of the installation
- Lay the walkway pads along the marked line
- If arranged in a row, move the pads against the two spacers
- Overlap the welding tabs in the running direction of the welding machine

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

0800 745 269  
www.sika.co.nz



## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.