

PRODUCT DATA SHEET

Sikafloor® Pronto Hardener

Hardener for Sikafloor® Pronto

DESCRIPTION

Hardener for Sikafloor® Pronto based on dibenzoyl peroxide.

USES

Sikafloor® Pronto Hardener may only be used by experienced professionals.

To harden all Sikafloor® Pronto products.

CHARACTERISTICS / ADVANTAGES

Part of the modular Sikafloor® Pronto products.

PRODUCT INFORMATION

Chemical Base	Dibenzoyl peroxide
Packaging	25 kg packs
Appearance / Colour	White powder
Shelf Life	12 months from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in cool and dry conditions at temperatures between +5 °C and +30 °C.

APPLICATION INFORMATION

Mixing Ratio	See product data sheet of the selected primer/coating.
Consumption	The amount of hardener required is dependent on the ambient and substrate temperature. See product data sheet of the selected primer/coating.
Ambient Air Temperature	+5 °C min. / +30 °C max.
Relative Air Humidity	80 % r.h. max.
Dew Point	Beware of condensation! The substrate and uncured floor must be at least 3 °C above dew point to reduce the risk of condensation or blooming on the floor finish.
Substrate Temperature	+5 °C min. / +30 °C max.

Substrate Moisture Content	See product data sheet of the selected primer.
Pot Life	See product data sheet of the selected primer/coating.
Curing Time	See product data sheet of the selected primer/coating.
Applied Product Ready for Use	See product data sheet of the selected primer/coating.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

See product data sheet of the selected primer.

MIXING

See product data sheet of the selected primer/coating.

APPLICATION

See product data sheet of the selected primer/coating.

CLEANING OF TOOLS

Clean all tools with Sika® Thinner C immediately after use. Hardened and/or cured material can only be removed mechanically.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited
85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz



Product Data Sheet
Sikafloor® Pronto Hardener
July 2026, Version 04.01
020813010010000013

SikafloorProntoHardener-en-NZ-(07-2026)-4-1.pdf

