

PRODUCT DATA SHEET

Sika® BituSeal Primer

BituSeal Primer

DESCRIPTION

Sika® BituSeal Primer is a bitumen solution to be used in conjunction with Sika® BituSeal S-115.

USES

Sika® BituSeal Primer is used as a primer for Sika® BituSeal S-115 to increase adhesion and bond to the substrate.

Sika® BituSeal Primer should be used as a primer for Sikaplan® - 1653 Adhered VOC Gas Barrier

CHARACTERISTICS / ADVANTAGES

- High adhesion and bonding ability on various substrates
- Good binding ability for dust and loose particles
- Ready to use by brush, roller or spray

PRODUCT INFORMATION

Chemical Base	Bitumen Solution
Packaging	25 ltr drums
Colour	Black liquid
Shelf Life	18 months from date of production.
Storage Conditions	Store in dry conditions between +5°C to +35°C. They must be protected from direct sunlight, rain, snow and ice.
Flash Point	> 39°C
Solid Content	48%
Viscosity	500 cP

APPLICATION INFORMATION

Consumption	Rate: approx. 350g/m ² depending on substrate type and temperature Coverage: 6-8m ² /ltr WFT: 90-110 microns DFT: 45-60 microns
--------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Application Method / Tools

Application by brush or roller.

Waiting time, depending to temperature, > 30min. unless drying.

For more detailed information, please refer to the current Method Statement of the according system.

Notes on Application / Limits

This product must not be installed on wet substrates.

Apply at temperatures above +10°C. At lower temperatures, use a hot air gun or indirect flame to aid adhesion.

Never attempt to apply at temperatures below +5°C.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited
85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz



Product Data Sheet
Sika® BituSeal Primer
December 2021, Version 01.01
020725601000000001

SikaBituSealPrimer-en-NZ-(12-2021)-1-1.pdf