


Note:
 Highly porous blocks and uneven masonry walls shall be bagged with Sika MonoTop Fairing Coat or other appropriate cement based mortar.
 All block joints shall be flush pointed.



Sika BlackSeal Elastic
 Masonry wall - ground level termination

General Detail. Not to scale.

DRAWING MUST ALWAYS BE REVIEWED BY A DESIGN SPECIALIST AND IF NECESSARY MODIFIED TO ENSURE SUITABILITY FOR THE SPECIFIC APPLICATION
 The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

900_NZ_020706_W014C_2503 en_NZ_03_2025
 March 2025

Sika (NZ) Ltd
 85-91 Patiki Rd, Avondale
 Auckland 1026
 New Zealand
 Tel: 0800 745 269
 www.sika.co.nz

