

**BUILDING TRUST** 

**CHARACTERISTICS / ADVANTAGES** 

Specifically graded and blended for use with Sika-

floor®-264 floor coating systems.

## PRODUCT DATA SHEET

# Sika<sup>®</sup> Aggregate-508

Component C for use with Sikafloor®-264 coating systems.

#### DESCRIPTION

A selection of carefully graded, kiln dried and blended natural aggregates.

### USES

Sika<sup>®</sup> Aggregate-508 is used as the Component C aggregate for Sikafloor<sup>®</sup>-264.

#### **PRODUCT INFORMATION**

Packaging	20 kg bags
Shelf Life	Twenty-four (24) months from date of production if stored correctly in un- opened, undamaged and original sealed packaging.
Storage Conditions	Store in dry and cool conditions. Protect from moisture.
Maximum Grain Size	Aggregate Grading: 0.1 - 0.3 mm
Bulk Density	~ 1.55 kg/litre (dry)

#### **BASIS OF PRODUCT DATA**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### FURTHER DOCUMENTS

Refer to the specific Sikafloor<sup>®</sup> MultiDur system data sheet for full information.

#### ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

Product Data Sheet Sika® Aggregate-508 December 2023, Version 01.02 020816010010000075

#### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited 85-91 Patiki Road Avondale, Auckland 1026 New Zealand 0800 745 269 www.sika.co.nz



 Product Data Sheet

 Sika® Aggregate-508

 December 2023, Version 01.02

 020816010010000075

SikaAggregate-508-en-NZ-(12-2023)-1-2.pdf

**BUILDING TRUST** 

