Sikadur-S Grout Fix (B)

Version 1.0



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	[:] Sikadur-S Grout Fix (B)			
Product code	: 000000607846			
Type of product	: liquid			
Manufacturer or supplier's details				
Company	: Sika (NZ) Ltd. 85-91 Patiki Road Avondale Auckland AKL 1026			
Telephone	: +64 9 820 2900			
Emergency telephone num- ber	: 0800 734 607			
Telefax	: +64 9 828 4091			
E-mail address	: info@nz.sika.com			

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	
6.3 Skin irritation	: Category A
6.4 Eye irritation	: Category A
6.5 Skin sensitisation	: Category B
6.9 Specific Target Organ Toxicity (Dermal)	: Category B
9.1 Aquatic toxicity (Acute or Chronic)	: Category B

GHS label elements

Hazard pictograms



Signal word : Warning

 Hazard statements
 : H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H371 May cause damage to organs in contact with skin. H411 Toxic to aquatic life with long lasting effects.
 Precautionary statements
 : Prevention: P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Sikadur-S Grout Fix (B)

Sikadur-S Grout Fix (B)		Jika
Version 1.0	SDS Number: 000000607846	Revision Date: 2018/02/01
	 P264 Wash skin thoroughly after har P270 Do not eat, drink or smoke whe P272 Contaminated work clothing shift the workplace. P273 Avoid release to the environme P280 Wear protective gloves/ eye proses P302 + P352 IF ON SKIN: Wash wit P305 + P351 + P338 IF IN EYES: R for several minutes. Remove contact easy to do. Continue rinsing. P309 + P311 IF exposed or if you fe CENTER or doctor/ physician. P321 Specific treatment (see supple on this label). P333 + P313 If skin irritation or rash vice/ attention. P362 Take off contaminated clothing P391 Collect spillage. Storage: P405 Store locked up. Disposal: P501 Dispose of contents/ container disposal plant. 	en using this product. hould not be allowed out of ent. rotection/ face protection. h plenty of soap and water. inse cautiously with water t lenses, if present and el unwell: Call a POISON mental first aid instructions occurs: Get medical ad- : Get medical advice/ at- g and wash before reuse.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 20 - < 30
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	>= 10 - < 20
2,3-epoxypropyl neodecanoate	26761-45-5	>= 1 - < 10

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately.

Sikadur-S Grout Fix (B)



Version 1.0	SDS Number: 000000607846	Revision Date: 201
	Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	 Immediately flush eye(s) with plenty of Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a special 	
If swallowed	: Clean mouth with water and drink after Do not give milk or alcoholic beverages Never give anything by mouth to an uno Obtain medical attention.	6.
Most important symptoms and effects, both acute and delayed	 irritant effects <pre>sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs in contact with skin.</pre>	
Notes to physician	: Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.	
Specific hazards during fire- fighting	: Do not allow run-off from fire fighting to enter drains or water courses.	
Hazardous combustion prod- ucts	: No hazardous combustion products are known	
Specific extinguishing meth- ods	 Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. 	
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

Sikadur-S Grout Fix (B)



Version 1.0	SDS Number: 000000607846	Revision Date: 2018/02/0
	respective authorities.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. s acid binder, universal binder, sawdust). Keep in suitable, closed containers for dispo	

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Hygiene measures	 Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	 Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	: Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling

Sikadur-S Grout Fix (B)

Version 1.0	SDS Number: 000000607846	Revision Date: 2018/02/01
	chemical products if a risk assessment indicates this is nec- essary.	
Eye protection	: Safety eyewear complying with an ap be used when a risk assessment indic	
Skin and body protection	: Choose body protection in relation to tration and amount of dangerous subscific work-place.	

®

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: white
Odour	: sweet
Odour Threshold	: No data available
рН	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: > 100 °C (> 212 °F)
Flash point	: No data available
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Upper explosion limit Lower explosion limit	No data availableNo data available
Lower explosion limit	: No data available
Lower explosion limit Vapour pressure	: No data available : 0.01 hPa (0.01 mmHg)
Lower explosion limit Vapour pressure Relative vapour density	No data available0.01 hPa (0.01 mmHg)No data available
Lower explosion limit Vapour pressure Relative vapour density Density Solubility(ies)	 No data available 0.01 hPa (0.01 mmHg) No data available 1.75 g/cm3 (20 °C (68 °F) ())
Lower explosion limit Vapour pressure Relative vapour density Density Solubility(ies) Water solubility Partition coefficient: n-	 No data available 0.01 hPa (0.01 mmHg) No data available 1.75 g/cm3 (20 °C (68 °F) ()) insoluble

Sikadur-S Grout Fix (B)

Version 1.0	SDS Number: 000000607846	Revision Date: 2018/02/01
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: >7 mm2/s (40 °C)	
Explosive properties	: No data available	
Molecular weight	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac- tions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecu- lar weight <= 700):	
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity	: LD50 Dermal (Rabbit): > 20,000 mg/kg
, louio donnar loviony	

2,3-epoxypropyl neodecanoate:

Acute oral toxicity	:	LD50 Oral (Rat): 9,600 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): 3,800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Sikadur-S Grout Fix (B)

Version 1.0



Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause damage to organs in contact with skin.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:	
· · ·	A-(epichlorhydrin) and epoxy resin (number average molecu-
lar weight <= 700): Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h
2,3-epoxypropyl neodecanoa Toxicity to daphnia and other aquatic invertebrates	te: : EC50 (Daphnia magna (Water flea)): 3.5 mg/l Exposure time: 48 h
Persistence and degradability No data available	/
Bioaccumulative potential No data available	
Mobility in soil No data available	
Other adverse effects	
Product: Additional ecological infor- mation	: Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Sikadur-S Grout Fix (B)

Revision Date: 2018/02/01

Version 1.0

Contaminated packaging

: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations IATA-DGR Not dangerous goods IMDG-Code Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations NZS 5433 Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002670

HSNO Controls

Certified handler certificate not required. HSNO tracking not required. Refer to EPA user guide to the HSNO control regulations for further information.

The components of this product are reported in the following inventories:

NZIOC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.