

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

### Section 1: Identification

Product name : Sikaflex®-406 KC

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

#### Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

### Section 2: Hazard identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

**Response:**

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**Hazardous components which must be listed on the label:**

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

Hardener LI (Isophoronedialdimine)  
Reaction product of Hexamethylene diisocyanate, oligomers with  
Mercaptopropyltrimethoxysilane  
Pentamethyl piperidylsebacate  
4,4'-methylenediphenyl diisocyanate  
m-tolyldiene diisocyanate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## Section 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

| Chemical name                                                                                 | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                    | Concentration<br>(% w/w) |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------|--------------------------|
| Hardener LI (Isophoronedialdimine)                                                            | 932742-30-8<br>700-071-4<br>01-2119880654-28-XXXX     | Skin Sens. 1B; H317<br>Aquatic Chronic 3;<br>H412 | >= 1 - < 2.5             |
| Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane | 192526-20-8<br>924-669-1<br>01-2120768758-32-XXXX     | Skin Sens. 1A; H317                               | >= 0.1 - < 0.5           |

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

|                                                                                                                                                              |                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| <p>Pentamethyl piperidylsebacate<br/>Contains:<br/>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate<br/>methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</p> | <p>1065336-91-5<br/>915-687-0<br/>01-2119491304-40-XXXX</p>              | <p>Skin Sens. 1A; H317<br/>Repr. 2; H361f<br/>Aquatic Acute 1; H400<br/>Aquatic Chronic 1; H410</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 1<br/>M-Factor (Chronic aquatic toxicity): 1</p>                                                                                                                                                                                                                                                                                                                                           | <p><math>\geq 0.1 - &lt; 0.25</math></p> |
| <p>4,4'-methylenediphenyl diisocyanate</p>                                                                                                                   | <p>101-68-8<br/>202-966-0<br/>615-005-00-9<br/>01-2119457014-47-XXXX</p> | <p>Acute Tox. 4; H332<br/>Skin Irrit. 2; H315<br/>Eye Irrit. 2; H319<br/>Resp. Sens. 1; H334<br/>Skin Sens. 1; H317<br/>Carc. 2; H351<br/>STOT SE 3; H335 (Respiratory system)</p> <hr/> <p>specific concentration limit<br/>Eye Irrit. 2; H319<br/><math>\geq 5 \%</math></p> <p>STOT SE 3; H335<br/><math>\geq 5 \%</math></p> <p>Skin Irrit. 2; H315<br/><math>\geq 5 \%</math></p> <p>Resp. Sens. 1; H334<br/><math>\geq 0.1 \%</math></p> <hr/> <p>Acute toxicity estimate</p> <p>Acute inhalation toxicity (dust/mist): 1.5 mg/l</p> | <p><math>&lt; 0.1</math></p>             |

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

|                           |                                                                  |                                                                                                                                                                                                                                                                                                                                                                                   |                    |
|---------------------------|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| m-tolylidene diisocyanate | 26471-62-5<br>247-722-4<br>615-006-00-4<br>01-2119454791-34-XXXX | Acute Tox. 1; H330<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Carc. 2; H351<br>STOT SE 3; H335<br>(Respiratory system)<br>Aquatic Chronic 3;<br>H412<br><br>specific concentration<br>limit<br>Resp. Sens. 1; H334<br>≥ 0.1 %<br><br>Acute toxicity esti-<br>mate<br><br>Acute inhalation tox-<br>icity (vapour): 0.107<br>mg/l | ≥ 0.025 - <<br>0.1 |
|---------------------------|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|

For explanation of abbreviations see section 16.

### Section 4: First-aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## Section 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## Section 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## Section 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Storage class (TRGS 510) : 10

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## Section 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                          | CAS-No.                                                                                                                                                                                                                                                                                                                                                                                                | Value type (Form of exposure)                 | Control parameters * | Basis *     |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|----------------------|-------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8                                                                                                                                                                                                                                                                                                                                                                                               | AGW (Vapour and aerosols)                     | 0.05 mg/m3           | TRGS 430    |
|                                     | Peak-limit: excursion factor (category): 1;=2=(I)                                                                                                                                                                                                                                                                                                                                                      |                                               |                      |             |
|                                     | Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance                                                                                                                                                                        |                                               |                      |             |
|                                     |                                                                                                                                                                                                                                                                                                                                                                                                        | AGW (Vapour and aerosols, inhalable fraction) | 0.05 mg/m3           | DE TRGS 900 |
|                                     | Peak-limit: excursion factor (category): 1;=2=(I)                                                                                                                                                                                                                                                                                                                                                      |                                               |                      |             |
|                                     | Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system |                                               |                      |             |
|                                     |                                                                                                                                                                                                                                                                                                                                                                                                        | MAK (inhalable fraction)                      | 0.05 mg/m3           | DE DFG MAK  |
|                                     | Peak-limit: excursion factor (category): 1; I                                                                                                                                                                                                                                                                                                                                                          |                                               |                      |             |
|                                     | Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed                                          |                                               |                      |             |
|                                     |                                                                                                                                                                                                                                                                                                                                                                                                        | Mow                                           | 0.1 mg/m3            | DE DFG MAK  |
|                                     | Peak-limit: excursion factor (category): 1; I                                                                                                                                                                                                                                                                                                                                                          |                                               |                      |             |

## SAFETY DATA SHEET

## Sikaflex®-406 KC

Version  
1.1Revision Date:  
29.07.2026SDS Number:  
100000020719Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

|                           |                                                                                                                                                                                                                                                         |                           |                          |             |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------|-------------|
|                           |                                                                                                                                                                                                                                                         | TWA                       | 0.01 mg/m3<br>(NCO)      | 98/24/EC I  |
|                           | Further information: Skin, Dermal and respiratory sensitisation, Binding                                                                                                                                                                                |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | STEL                      | 0.02 mg/m3<br>(NCO)      | 98/24/EC I  |
| m-tolylidene diisocyanate | 26471-62-5                                                                                                                                                                                                                                              | AGW                       | 0.005 ppm<br>0.035 mg/m3 | TRGS 430    |
|                           | Peak-limit: excursion factor (category): 1;=4=(I)                                                                                                                                                                                                       |                           |                          |             |
|                           | Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance                         |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | AGW (Vapour and aerosols) | 0.005 ppm<br>0.035 mg/m3 | DE TRGS 900 |
|                           | Peak-limit: excursion factor (category): 1;=4=(I)                                                                                                                                                                                                       |                           |                          |             |
|                           | Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | AGW                       | 0.005 ppm<br>0.035 mg/m3 | DE TRGS 900 |
|                           |                                                                                                                                                                                                                                                         | MAK                       | 0.001 ppm<br>0.007 mg/m3 | DE DFG MAK  |
|                           | Peak-limit: excursion factor (category): 1; I                                                                                                                                                                                                           |                           |                          |             |
|                           | Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed                                                                                    |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | Mow                       | 0.005 ppm<br>0.035 mg/m3 | DE DFG MAK  |
|                           | Peak-limit: excursion factor (category): 1; I                                                                                                                                                                                                           |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | TWA                       | 0.01 mg/m3<br>(NCO)      | 98/24/EC I  |
|                           | Further information: Skin, Dermal and respiratory sensitisation, Binding                                                                                                                                                                                |                           |                          |             |
|                           |                                                                                                                                                                                                                                                         | STEL                      | 0.02 mg/m3<br>(NCO)      | 98/24/EC I  |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

| Substance name                                                                                | End Use   | Exposure routes | Potential health effects   | Value     |
|-----------------------------------------------------------------------------------------------|-----------|-----------------|----------------------------|-----------|
| Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane | Workers   | Inhalation      | Long-term systemic effects | 1.7 mg/m3 |
|                                                                                               | Workers   | Dermal          | Long-term systemic effects | 4.7 mg/kg |
|                                                                                               | Consumers | Inhalation      | Long-term systemic effects | 0.3 mg/m3 |
|                                                                                               | Consumers | Dermal          | Long-term systemic effects | 1.7 mg/kg |

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

| Substance name                    | Environmental Compartment | Value    |
|-----------------------------------|---------------------------|----------|
| Reaction product of Hexamethylene | Fresh water               | 0.1 mg/l |

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

|                                                                  |                          |             |
|------------------------------------------------------------------|--------------------------|-------------|
| diisocyanate, oligomers with Mercapto-<br>propyltrimethoxysilane |                          |             |
|                                                                  | Intermittent use/release | 1 mg/l      |
|                                                                  | Marine water             | 0.01 mg/l   |
|                                                                  | Intermittent use/release | 1 mg/l      |
|                                                                  | Fresh water sediment     | 23.28 mg/kg |
|                                                                  | Marine sediment          | 2.33 mg/kg  |
|                                                                  | Sewage treatment plant   | 100 mg/l    |
|                                                                  | Soil                     | 4.58 mg/kg  |

### 8.2 Exposure controls

#### Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Safety glasses with side-shields conforming to EN166
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Form : paste
- Colour : black
- Odour : none



# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C  
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : ca. 42,000 mPa.s (20 °C)

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0.01 hPa

Density : ca. 1.40 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

## Section 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

## Section 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **Hardener LI (Isophoronedialdimine):**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

##### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3,230 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 1.5 mg/l  
Test atmosphere: dust/mist  
Method: ATE value derived from LD50/LC50 value

##### **m-tolylidene diisocyanate:**

Acute inhalation toxicity : LC50 (Rat): 0.107 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute toxicity estimate: 0.107 mg/l  
Test atmosphere: vapour  
Method: Calculation method

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

### **Skin corrosion/irritation**

Not classified due to lack of data.

### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

Not classified due to lack of data.

#### **STOT - repeated exposure**

Not classified due to lack of data.

#### **Aspiration hazard**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified due to lack of data.

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **Section 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

##### **Hardener LI (Isophoronedialdimine):**

Toxicity to fish : LC50 (Fish): 87.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 180.4 mg/l  
plants Exposure time: 72 h

##### **Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### **Pentamethyl piperidylsebacate:**

Toxicity to fish : LC50 (Fish): 0.97 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological information : There is no data available for this product.

## **Section 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.  
Completely emptied packagings may be given for recycling.  
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.  
Sika has agreed disposal contracts for all packaging which is

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

brought into circulation in Germany.  
For further details see [www.sika.de](http://www.sika.de)

### Section 14: Transport information

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Section 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 20: dibutyltin dilaurate

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

Number on list 40

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich

Number on list 74:

4,4'-methylenediphenyl diisocyanate, m-tolylidene diisocyanate

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Water hazard class (Germany) : WGK 1 slightly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Not applicable

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

### Other regulations:

Product is no subject to the Chemicals Prohibition Ordinance.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### HSNO Approval Number

HSR002670

### Tolerable Exposure Limits (TEL)

Not applicable

### Environmental Exposure Limits (EEL)

Not applicable

### HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZ NZIoC : On the inventory, or in compliance with the inventory

### Section 16: Other information

#### Full text of H-Statements

|       |                                                                              |
|-------|------------------------------------------------------------------------------|
| H315  | : Causes skin irritation.                                                    |
| H317  | : May cause an allergic skin reaction.                                       |
| H319  | : Causes serious eye irritation.                                             |
| H330  | : Fatal if inhaled.                                                          |
| H332  | : Harmful if inhaled.                                                        |
| H334  | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335  | : May cause respiratory irritation.                                          |
| H351  | : Suspected of causing cancer.                                               |
| H361f | : Suspected of damaging fertility.                                           |
| H400  | : Very toxic to aquatic life.                                                |
| H410  | : Very toxic to aquatic life with long lasting effects.                      |
| H412  | : Harmful to aquatic life with long lasting effects.                         |

#### Full text of other abbreviations

|                 |                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------|
| Acute Tox.      | : Acute toxicity                                                                          |
| Aquatic Acute   | : Short-term (acute) aquatic hazard                                                       |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard                                                      |
| Carc.           | : Carcinogenicity                                                                         |
| Eye Irrit.      | : Eye irritation                                                                          |
| Repr.           | : Reproductive toxicity                                                                   |
| Resp. Sens.     | : Respiratory sensitisation                                                               |
| Skin Irrit.     | : Skin irritation                                                                         |
| Skin Sens.      | : Skin sensitisation                                                                      |
| STOT SE         | : Specific target organ toxicity - single exposure                                        |
| 98/24/EC I      | : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values |
| DE DFG MAK      | : Germany. MAK BAT Annex IIa                                                              |
| DE TRGS 900     | : Germany. TRGS 900 - Occupational exposure limit values.                                 |

# SAFETY DATA SHEET

## Sikaflex®-406 KC



Version  
1.1

Revision Date:  
29.07.2026

SDS Number:  
100000020719

Date of last issue: 11.11.2025  
Date of first issue: 11.11.2025

|                   |                                                                                                                                                                                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TRGS 430          | : Germany. TRGS 430 - Isocyanates                                                                                                                                                                                                      |
| 98/24/EC I / STEL | : Limit values Short-term                                                                                                                                                                                                              |
| 98/24/EC I / TWA  | : Limit values 8 hours                                                                                                                                                                                                                 |
| DE DFG MAK / Mow  | : Momentary value                                                                                                                                                                                                                      |
| DE DFG MAK / MAK  | : MAK value                                                                                                                                                                                                                            |
| DE TRGS 900 / AGW | : Time Weighted Average                                                                                                                                                                                                                |
| TRGS 430 / AGW    | : Occupational Exposure Limit                                                                                                                                                                                                          |
| ADR               | : European Agreement concerning the International Carriage of Dangerous Goods by Road                                                                                                                                                  |
| CAS               | : Chemical Abstracts Service                                                                                                                                                                                                           |
| DNEL              | : Derived no-effect level                                                                                                                                                                                                              |
| EC50              | : Half maximal effective concentration                                                                                                                                                                                                 |
| GHS               | : Globally Harmonized System                                                                                                                                                                                                           |
| IATA              | : International Air Transport Association                                                                                                                                                                                              |
| IMDG              | : International Maritime Code for Dangerous Goods                                                                                                                                                                                      |
| LD50              | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)                                                                                               |
| LC50              | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL            | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL               | : Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT               | : Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC              | : Predicted no effect concentration                                                                                                                                                                                                    |
| REACH             | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC              | : Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB              | : Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

#### Classification of the mixture:

Skin Sens. 1

H317

#### Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

DE / EN