

BUILDING PRODUCT INFORMATION SHEET

Sikasil® Wet Areas

Alcoxy Silicone Sealant

DESCRIPTION

Sikasil® Wet Areas is a one-component neutral curing silicone sealant suitable for wet area applications. It is used as a joint sealant between a variety of substrates.

USES

Sikasil® Wet Areas is a highly durable silicone rubber that has excellent long term performance in wet areas where there is high humidity, including commercial and residential bathrooms and toilets, showers and wash down areas, kitchens and laundries.

Sikasil® Wet Areas has good resistance to the growth of mould and fungus on its surface. It is highly elastic and flexible and has very strong adhesion to a wide variety of “wet room” surfaces including:

- Porcelain whiteware and fittings
- Painted surfaces
- Ceramic tiles and grouts
- Glass
- Plastic laminates
- Stainless steel

- Rigid PVC, acrylics, polycarbonate
- Metal, copper and brass fittings
- Powder coated aluminium
- Concrete

FEATURES

- Highest quality, non-sag
- Excellent adhesion to a wide range of substrates
- Highly elastic +/-25%
- Excellent UV resistance
- Non-corrosive
- Fast curing
- Low odour

APPROVALS / CERTIFICATES

Complies with ISO 11600 – Type F – Class 25LM and ISO 11600 – Type G - Class 25 LM. Suitable for use under Clause E3 of the Building Code – Internal Moisture.

PRODUCT INFORMATION

Product identifier	Sikasil® Wet Areas
Place of manufacture	Aotearoa New Zealand
Composition	Alcoxy
Packaging	300ml cartridges, 12 cartridges per box
Shelf life	18 months from date of production when stored as stated below.
Storage conditions	Store in cool, dry conditions in original unopened containers.
Colour	Translucent, white
Density	Translucent: ~ 1.02 g/cm ³ (DIN 51757)

TECHNICAL INFORMATION

Shore A hardness	~ 22 (ISO 868)
-------------------------	----------------

Tensile strength	~ 0.50 - 0.70 N/mm ²	(ISO 8339)
Modulus of elasticity in tension	~ 0.35 - 0.40 N/mm ² (at 100% elongation)	(ISO 8339)
Tensile strain at break	~ 250%	(ISO 8339)
Movement capability	+/- 25 %	(ISO 9047)
Elastic recovery	> 90 %	
Tear strength	~ 4.6 N/mm	(ISO 34 Method C)
Joint design	The sealant joint width should be designed to accommodate the movement capability of the sealant. In general, minimum joint width should be 6 mm. For joints between 6 - 12 mm wide, a seal depth of 6mm is recommended. For joints greater than 12 mm wide, a width to depth ratio of 2 : 1 is recommended.	

APPLICATION INFORMATION

APPLICATION

- For best results apply masking tape to both sides of the joint before sealing and remove masking tape before silicone skins.
- Cut tip off nozzle at 45 angle and gun sealant into joint.
- The sealant should be tooled smooth within 5-10 minutes, or before surface skins, using a spatula which has been dipped into diluted soapy water.
- Masking tape is then removed immediately.

Ambient air temperature	Application temp.: + 5°C to + 40°C.	
Curing rate	1 day: ~2 mm	(23° C, 50% R.H.)
Skinning time	~ 25 minutes	(23°C, 50% R.H.)

MANUFACTURER AND IMPORTER INFORMATION

Manufacturer information	Address	Sika (NZ) Limited 85-91 Patiki Road Avondale, Auckland 1026 New Zealand
	Phone number	0800 745 269
	Website	https://nzl.sika.com/
	Email address	info@nz.sika.com
	NZBN	9429000018791

BUILDING CODE INFORMATION

Building Code clauses	B2 Durability: Performance clauses B2.3.1 - (b) not less than 15 Years, (c) not less than 5 years E2 External Moisture: Performance clause E2.3.2 E3 Internal Moisture: Performance Clauses E3.3.3, E3.3.4, E3.3.5, E3.3.6 F2 Hazardous Building Materials: Performance clause F2.3.1
Building Code compliance statements	Performance B2.3.1 (b) 15 years and (c) 5 years: This product achieves these durability requirements and will remain serviceable for 15 years, or more, when installed and maintained in accordance with the relevant Sika technical literature. nzl.sika.com . According to Sika's "Service Improvement" records, maintained within its ISO9001:2015 Quality Management System, this product has performed successfully since it was introduced in 2005. Performance E2.3.1, E2.3.2: In accordance with E2/AS1 and E2/AS3 (CCANZ CP 01:2014) this product has been tested and is compliant with the ISO11600:2002 Type F, Class 25LM classification (refer to nzl.sika.com). When used to seal flexible joints, as part of a roofing or wall cladding system, or around external openings, such as windows and doors, the product contributes to meeting the E2.3.1 and E2.3.2 weathertightness requirements.

NZ BUILDING PRODUCT INFORMATION SHEET

Sikasil® Wet Areas
12/12/2024 File version 1.0
020514030000000024

Performance E3.3.3, E3.3.4, E3.3.5, E3.3.6: This product has been tested and is compliant with the ISO11600:2002 Type F, Class 25LM classification. When used to form impervious and easy to clean joints between sheet lining materials and between fixtures and linings, as defined in E3/AS1, it contributes to meeting these impermeability requirements.

Performance F2.3.1: This product meets this requirement when used and applied in accordance with Sika's installation instructions and does not present a health hazard to people occupying or using the building. Refer to the Sika Product Technical Data sheet and product Safety Data Sheet nzl.sika.com for further information if required

BASIS OF PRODUCT DATA

All technical data in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Do not use on bituminous substrates, natural rubber, chloroprene or EPDM
- Limitations on building materials which might bleed oils, plasticizers or solvents.
- Do not use in a totally confined space, because the sealant requires atmospheric moisture to cure.
- Bleeding can occur on porous substrates such as concrete, marble, granite and other natural stones. On sensitive substrates, specific testing should be carried out.
- Not recommended for use in submerged joints or in joints where mechanical damage or abrasion are likely to occur.
- Do not use in fish tanks.
- Not recommended for structural glazing or insulated glazing applications.
- Not suitable for food contact applications.
- Sikasil® Wet Areas is neither tested nor represented as suitable for medical or pharmaceutical uses.
- Refer to the "Sikaflex Elastomeric Sealants" guide for information on joint design and calculation of joint movement.
- Regular cleaning is required to prevent the accumulation of excessive soap and other contamination that could support the growth of mould and fungus.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

DESIGN REQUIREMENTS

Sikaflex Elastomeric Sealants - Joint design and movement calculation guide nzl.sika.com

Sika Sealant Selector Guide, Consumption Guide and Best Practice Tips nzl.sika.com

SUBSTRATE PREPARATION

Surfaces must be clean, dry and free from loose particles, grease and dirt. Degrease surface with Sika Thinner C if necessary. Allow the surface to dry (i.e. the solvent to fully evaporate) before proceeding.

CLEANING OF EQUIPMENT

Uncured material can be removed by using a suitable solvent or an approved sealant remover such as Sika Thinner C, Acetone or MEK. Cured material may be removed by abrasion or other mechanical means.

MAINTENANCE REQUIREMENTS

Joints that have been sealed with this product should be inspected annually (or sooner if required). Gently clean the surface of the joint with a mild solution of water and household detergent, using a soft brush to remove any residual contaminants and rinse clean with fresh water. Any defects within the joint should be identified and removed. The joint should then be cleaned, primed and repaired using the same Sika product to restore the original integrity of the joint. Refer to the Sika product data sheet and the website for further information. nzl.sika.com

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above dis-

NZ BUILDING PRODUCT INFORMATION SHEET

Sikasil® Wet Areas
12/12/2024 File version 1.0
020514030000000024

claimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

The building product/building product line is not subject to warning or ban under section 26 of the Building Act 2004.

Sika (NZ) Limited

85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz

NZ BUILDING PRODUCT INFORMATION SHEET

Sikasil® Wet Areas
12/12/2024 File version 1.0
020514030000000024

NZBPIS-4903-7502-7502-en-GB-1.0

