# Pulastic® EG/SO (B)



Date of last issue: 2021/12/09 Version **Revision Date:** SDS Number: 2022/08/29 000000214439 Date of first issue: 2015/06/26 6.0

#### **Section 1: Identification**

Product name Pulastic® EG/SO (B)

### Manufacturer or supplier's details

Company Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address info@nz.sika.com

Telefax +64 9 828 4091

### Recommended use of the chemical and restrictions on use

Product use : Flooring system, For professional users only.

### Section 2: Hazard identification

**GHS Classification** 

Acute toxicity (Inhalation) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 2

Respiratory sensitisation Category 1

Skin sensitisation Category 1

Carcinogenicity Category 2

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

Specific target organ toxicity - : Category 2

repeated exposure

# **GHS** label elements

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

Hazard pictograms :





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure.

Precautionary statements

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

P284 Wear respiratory protection.

## Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Doctor if you reer driwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ at-

ention.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

#### Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture :

Mixture

Components

| Chemical name                                  | CAS-No.    | Concentration (% w/w) |  |
|--|------------|-----------------------|--|
| 4,4`-Methylenediphenyl diisocyanate, oligomers | 25686-28-6 | >= 70 -< 90           |  |
| aromatic isocyanate-prepolymer                 | 9048-57-1  | >= 30 -< 50           |  |

#### Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects

Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Headache Dermatitis

# Pulastic® EG/SO (B)



Date of last issue: 2021/12/09 Version **Revision Date:** SDS Number: 2022/08/29 000000214439 Date of first issue: 2015/06/26 6.0

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Section 6: Accidental release measures

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

## Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

| Components                    | CAS-No.  | Value type | Control parame-    | Basis  |  |
|-------------------------------|--|------------|--------------------|--------|--|
|                               |  | (Form of   | ters / Permissible |        |  |
|                               |  | exposure)  | concentration      |        |  |
| 4,4`-Methylenediphenyl diiso- | 25686-28-6   | WES-TWA    | 0.02 mg/m3         | NZ OEL |  |
| cyanate, oligomers            |  |            | (NCO)              |        |  |
|                               | Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as va- |            |                    |        |  |
|                               | pours, mist or dust.   |            |                    |        |  |
|                               |  | WES-STEL   | 0.07 mg/m3         | NZ OEL |  |
|                               |  |            | (NCO)              |        |  |

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

# Section 9: Physical and chemical properties

Appearance : liquid

Colour : yellow

Odour : slight

Odour Threshold : No data available

pH : Not applicable substance/mixture reacts with water

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : 195 °C (383 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.21 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n- : No data available

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

15 g/l

A+B Combined

# Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

# **Section 11: Toxicological information**

#### **Acute toxicity**

Harmful if inhaled.

## **Components:**

# 4,4`-Methylenediphenyl diisocyanate, oligomers:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

# aromatic isocyanate-prepolymer:

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### **Chronic toxicity**

# Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

# STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

### Section 12: Ecological information

### **Ecotoxicity**

### **Components:**

#### aromatic isocyanate-prepolymer:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1,000 mg/l

Exposure time: 96 h

#### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

# Pulastic® EG/SO (B)



Version **Revision Date:** SDS Number: Date of last issue: 2021/12/09 000000214439 Date of first issue: 2015/06/26 2022/08/29 6.0

## Mobility in soil

No data available

#### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

There is no data available for this product.

#### Section 13: Disposal considerations

#### **Disposal methods**

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

#### **Section 14: Transport information**

## International Regulations

#### **IATA-DGR**

Not applicable UN/ID No. Proper shipping name Not applicable Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Packing instruction (cargo Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

**IMDG-Code** 

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Not applicable Labels **EmS Code** Not applicable Marine pollutant Not applicable

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

**NZS 5433** 

**UN** number Not applicable

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

Proper shipping name : Not applicable Class : Not applicable Subsidiary risk : Not applicable Packing group : Not applicable Labels : Not applicable Hazchem Code : Not applicable

Special precautions for user

Not applicable

## **Section 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

### **HSNO Approval Number**

HSR002679

#### **HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

### **Section 16: Other information**

## Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

# Pulastic® EG/SO (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/12/09

 6.0
 2022/08/29
 000000214439
 Date of first issue: 2015/06/26

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN