



Hydrotech® Surface Conditioner 56170

GENERAL DESCRIPTION

An asphalt-based conditioner for use on concrete substrates.

BASIC USE

To enhance the bond of Hydrotech® Monolithic Membrane 6125® roofing and waterproofing membranes to concrete substrates.

TECHNICAL SPECIFICATIONS

Must conform to CGSB 37-GP-9Ma.

SIZES

Hydrotech Surface Conditioner 56170 is available in 20 ltr drums. Coverage 1.2 litres per / 10m².



APPLICATION

- Thoroughly clean area to be waterproofed. The area must be thoroughly swept, then blown clean using an air compressor.
- The Surface Conditioner is then spray-applied at a rate of 300-600 square feet per gallon (7.36 – 14.72 m²/l). The result should be a “tanning” of the concrete surface. Over-application may cause adhesion problems between the concrete and Hydrotech Monolithic Membrane 6125.
- The Surface Conditioner must be allowed sufficient time to thoroughly dry. **NOTE:** The cooler the ambient temperature and/or higher the humidity, the more drying time required.
- **DO NOT** apply Surface Conditioner to wood, plywood, metal or gypsum board substrates - concrete only.
- The Surface Conditioner can be cut-back with unleaded petrol if necessary, to facilitate spraying.

CAUTIONS

FLAMMABLE MATERIAL!

Do not use near open fire or flame and extinguish all smoking materials.

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Montreal, QC
Extraction/Harvesting Location		Montreal, QC

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any Other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and Regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited
85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz