

Only to be applied by a Sika Approved Applicator



Sikalastic® Carrier

Glass Reinforced Carrier Membrane

Product Description	Sikalastic® Carrier incorporates a dimensionally stable glass reinforcement and a modified elastomer coating, providing a highly effective carrier membrane.	
Uses	<ul style="list-style-type: none"> Sikalastic® Carrier is for use on Sikalastic® Insulation in the SikaRoof® MTC Cold Bonding Systems. Sikalastic® Carrier is suitable for use on boarded decks for the application of SikaRoof® MTC 8, 12, 18 and 22. 	
Product Data		
Form	Rolls	
Dimensions	20 m x 1m	
Weight	36 kg/Roll	
Load at rupture	Longitudinal:	300 N/50 mm
	Transverse:	250 N/50 mm
Elongation at break	Longitudinal:	3%
	Transverse:	3%
Tearing nail test	Longitudinal:	25 N
	Transverse:	22.5 N
Storage Conditions	Store in original packing in a location free from any ignition hazard, such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat.	
Notes	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.	
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.	
Health & Safety Instructions		
Protective Measures	<ul style="list-style-type: none"> To avoid rare allergic reactions, we recommend the use of protective gloves. Change soiled work clothes and wash hands before breaks and after finishing work. Local regulations as well as health and safety advice on packaging labels must be observed. For further information refer to the Sika Material Safety Data Sheet which is available on request. If in doubt always follow the directions given on the pack or label. 	
Important Notes	<ul style="list-style-type: none"> Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities. Detailed health and safety information as well as detailed precautionary measures e.g. physical, toxicological and ecological data can be obtained from the safety data sheet. 	



Construction

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika (NZ) Ltd
PO Box 19192
Avondale
Auckland

Phone: 0800 SIKA NZ 0800 745 269
Fax: 0800 SIKA FAX 0800 745 232

