

PRODUCT DATA SHEET

Sika® Aggregate-505

BROADCASTING AGGREGATE FOR FLOORING APPLICATIONS

DESCRIPTION

A selection of carefully graded, kiln dried and blended natural aggregates

USES

Sika® Aggregates have been specifically developed for compatible use with a range of Sika products to provide a selection of non-skid surfaces that will help promote safety in the work place. Sika® Aggregate-505 is scattered liberally over Sikafloor®-264 (base coat) at a uniform rate and then a sealer coat is applied to achieve a minimally textured non-slip surface. Sika® Aggregate-505 can also be used over Sikafloor®-81 EpoCem and left as a finished non-slip surface, or subsequently overcoated with a selected Sikagard® or Sikafloor® epoxy coating.

CHARACTERISTICS / ADVANTAGES

- Compatible with Sikagard® and Sikafloor® flooring and coating systems.
- Provides a very fine textured, slip-resistant floor finish.

PRODUCT INFORMATION

Packaging	25 kg bags
Shelf Life	Twenty-four (24) months from date of production if stored in unopened, undamaged and original sealed packaging.
Storage Conditions	Store in dry and cool conditions. Protect from moisture.
Density	Dry, bulk density: 1.4 kg/litre approximately
Maximum Grain Size	Aggregate grading: 0.1 - 0.5 mm

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika (NZ) Limited
85-91 Patiki Road
Avondale, Auckland 1026
New Zealand
0800 745 269
www.sika.co.nz



SikaAggregate-505-en-NZ-(03-2019)-1-1.pdf

Product Data Sheet
Sika® Aggregate-505
March 2019, Version 01.01
020816010010000072

