

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika Primer-3 N
Product code : 000000120488
Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent, Primer

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026
Telephone : +64 9 820 2900
Emergency telephone number : 0800 734 607
Telefax : +64 9 828 4091
E-mail address : info@nz.sika.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

3.1 Flammable Liquids : Category B
6.1 Acute toxicity (Oral) : Category D
6.1 Acute toxicity (Inhalation) : Category E
6.3 Skin irritation : Category B
6.4 Eye irritation : Category A
6.7 Carcinogenicity : Category B
6.8 Toxic to Reproduction : Category B
6.9 Specific Target Organ Toxicity (Oral) : Category B
6.9 Specific Target Organ Toxicity (Inhalation) : Category B
9.1 Aquatic toxicity (Acute or Chronic) : Category D
9.3 Ecotoxic to terrestrial vertebrates : Category C

GHS label elements

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H333 May be harmful if inhaled.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs if swallowed.
H371 May cause damage to organs if inhaled.
H402 Harmful to aquatic life.
H433 Harmful to terrestrial vertebrates.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P312 IF INHALED: Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.
P330 Rinse mouth.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
ethyl acetate	141-78-6	>= 50 - < 70
xylene	1330-20-7	>= 1 - < 10
propan-2-ol	67-63-0	>= 1 - < 10
ethylbenzene	100-41-4	>= 1 - < 10
methanol	67-56-1	>= 0.1 - < 1
dibutyltin dilaurate	77-58-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : irritant effects
Excessive lachrymation
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
Harmful if swallowed.

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

Causes mild skin irritation.
Causes serious eye irritation.
May be harmful if inhaled.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs if swallowed.
May cause damage to organs if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use water spray to cool unopened containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	WES-TWA	200 ppm 720 mg/m ³	NZ OEL
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m ³	NZ OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
propan-2-ol	67-63-0	WES-TWA	400 ppm 983 mg/m ³	NZ OEL
		WES-STEL	500 ppm 1,230 mg/m ³	NZ OEL
ethylbenzene	100-41-4	WES-STEL	125 ppm 543 mg/m ³	NZ OEL
		WES-TWA	100 ppm 434 mg/m ³	NZ OEL
methanol	67-56-1	WES-STEL	250 ppm 328 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption			
		WES-TWA	200 ppm 262 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption			

Personal protective equipment

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : very faint
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : ca. -4 °C (25 °F)
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : 7 %(V)
- Lower explosion limit : 1 %(V)
- Vapour pressure : 99.9915 hPa (75.000 mmHg)
- Relative vapour density : No data available
- Density : ca. 0.98 g/cm³ (20 °C (68 °F) ())

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: ca. 10 mPa.s (20 °C)
Viscosity, kinematic	: < 20.5 mm ² /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.
May be harmful if inhaled.

Components:

ethyl acetate:

Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): ca. 1,600 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5,000 mg/kg

xylene:

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): < 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

methanol:

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Converted acute toxicity point estimate

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

Skin corrosion/irritation

Causes mild skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause damage to organs if swallowed.
May cause damage to organs if inhaled.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.3 mg/l
Exposure time: 96 h

dibutyltin dilaurate:

Toxicity to fish : LC50 (Fish): 3.1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002669

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

SAFETY DATA SHEET

Sika Primer-3 N



Version 1.2

SDS Number: 000000120488

Revision Date: 2019/07/07

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.