

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika Nailbond PB
Product code : 000000607610
Type of product : paste

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026
Telephone : +64 9 820 2900
Emergency telephone number : 0800 734 607
Telefax : +64 9 828 4091
E-mail address : info@nz.sika.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

3.1 Flammable Liquids : Category B
6.1 Acute toxicity (Oral) : Category E
6.3 Skin irritation : Category A
6.8 Toxic to Reproduction : Category B
9.1 Aquatic toxicity (Acute or Chronic) : Category C

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H361 Suspected of damaging fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P321 Specific treatment (see supplemental first aid instructions on this label).
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 10 - < 20
ethanol	64-17-5	>= 1 - < 10
Hydrocarbons, C9, aromatics	64742-95-6	>= 1 - < 2.5
toluene	108-88-3	>= 0.1 - < 0.25

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

	Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Risk of serious damage to the lungs (by aspiration). irritant effects Aspiration may cause pulmonary oedema and pneumonitis. Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms. May be fatal if swallowed and enters airways. Causes skin irritation. Suspected of damaging fertility or the unborn child.
Notes to physician	: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: Water High volume water jet
Specific hazards during fire-fighting	: Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use water spray to cool unopened containers.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures	: Use personal protective equipment. Remove all sources of ignition.
---	---

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

agency procedures Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	WES-TWA	1,000 ppm 1,880 mg/m ³	NZ OEL
		TWA	1,000 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C9, aromatics	64742-95-6	TWA	200 mg/m ³	ACGIH

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

			(total hydrocarbon vapor)	
toluene	108-88-3	WES-TWA	50 ppm 188 mg/m3	NZ OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : beige
- Odour : aromatic
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : 68 °C (154 °F)
- Flash point : -1 °C (30 °F)
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : 7.4 %(V)

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

Lower explosion limit	: 1.1 %(V)
Vapour pressure	: 34.6637 hPa (26.000 mmHg) 34.6637 hPa (26.000 mmHg)
Relative vapour density	: No data available
Density	: 1.05 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 7 mm ² /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : III
Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1133
Proper shipping name : ADHESIVES
- Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

- UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : III
Labels : 3

SAFETY DATA SHEET

Sika Nailbond PB



Version 1.0

SDS Number: 000000607610

Revision Date: 2018/08/26

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002662

HSNO Controls

Certified handler certificate required
HSNO tracking not required.
Refer to EPA user guide to the HSNO control regulations for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.