# **Icosit KC 330 Primer**



Version **Revision Date:** SDS Number: Date of last issue: 2018/12/13 2020/03/01 000000004192 Date of first issue: 2018/12/13 2.0

#### **Section 1: Identification**

Product name : Icosit KC 330 Primer

Product code : 00000004192

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900 : 0800 734 607

Emergency telephone num-

ber

Telefax : +64 9 828 4091 E-mail address : info@nz.sika.com

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

#### Section 2: Hazard identification

**GHS Classification** 

Flammable Liquids 3.1C

Acute toxicity (Inhalation) 6.1D

Skin irritation 6.3A

Eye irritation 6.4A

Respiratory sensitisation 6.5A

Skin sensitisation 6.5B

Carcinogenicity 6.7B

Acute toxicity 6.1E

Specific Target Organ Toxicity:

(Inhalation)

6.9B

Aquatic toxicity (Acute or

9.1C

Chronic)

#### **GHS** label elements

### **Icosit KC 330 Primer**



Version Revision Date: SDS Number: Date of last issue: 2018/12/13 000000004192 Date of first issue: 2018/12/13 2020/03/01 2.0

Hazard pictograms







Signal word Danger

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smokina.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P321 Specific treatment (see supplemental first aid instructions

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

on this label).

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards which do not result in classification

None known.

#### Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 10 -< 20
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 10 -< 20
homologues		
2-methoxy-1-methylethyl acetate	108-65-6	>= 10 -< 20
Hydrocarbons, C9, aromatics	64742-95-6	>= 10 -< 20
ethylbenzene	100-41-4	>= 1 -< 10

#### Section 4: First-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

# **Icosit KC 330 Primer**



SDS Number: Version **Revision Date:** Date of last issue: 2018/12/13 2020/03/01 000000004192 2.0 Date of first issue: 2018/12/13

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and delayed

irritant effects sensitising effects Asthmatic appearance

Cough

Respiratory disorder Allergic reactions **Excessive lachrymation** 

Headache Dermatitis Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eve irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Treat symptomatically. Notes to physician

### Section 5: Fire-fighting measures

Alcohol-resistant foam Suitable extinguishing media

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

Specific hazards during fire-

fighting

High volume water jet

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod: :

No hazardous combustion products are known

Specific extinguishing meth-Use water spray to cool unopened containers.

Special protective equipment:

In the event of fire, wear self-contained breathing apparatus.

for firefighters

### Section 6: Accidental release measures

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

# **Icosit KC 330 Primer**



Date of last issue: 2018/12/13 Version Revision Date: SDS Number: 000000004192 2020/03/01 Date of first issue: 2018/12/13 2.0

**Environmental precautions** Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

### Section 7: Handling and storage

Advice on protection against

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
xylene	1330-20-7	WES-TWA	50 ppm NZ OEL 217 mg/m3		
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	WES-TWA	0.02 mg/m3 (NCO)	NZ OEL	
	Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.				
		WES-STEL	0.07 mg/m3 (NCO)	NZ OEL	
	Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as va-				
	pours, mist or				
Hydrocarbons, C9, aromatics	64742-95-6	WES-TWA	300 ppm 890 mg/m3	NZ OEL	
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL	
ethylbenzene	100-41-4	WES-STEL	125 ppm 543 mg/m3	NZ OEL	
		WES-TWA	100 ppm 434 mg/m3	NZ OEL	

#### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhip- puric acid	Urine	End of shift	1.5 g/l	NZ BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after ex- posure ceases)	0.15 g/g creatinine	ACGIH BEI

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

# Section 9: Physical and chemical properties

Appearance : liquid
Colour : light brown
Odour : solvent-like
Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

Boiling point/boiling range : No data available

Flash point : ca. 25 °C (77 °F)

(Method: closed cup)

No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower

flammability limit

0.8 %(V)

Vapour pressure : 7.9993 hPa

Relative vapour density : No data available

Density : ca. 1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : 333 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C (104 °F))

Explosive properties : No data available

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

Oxidizing properties : No data available

# Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions: Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available No decomposition if stored and applied as directed.

### **Section 11: Toxicological information**

#### **Acute toxicity**

Harmful if inhaled.

### **Components:**

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### **Chronic toxicity**

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified based on available information.

#### Section 12: Ecological information

#### **Ecotoxicity**

plants

plants

### **Components:**

### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

EC50 (Desmodesmus subspicatus (green algae)): > 1,640

mg/l

Exposure time: 72 h

### Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

mg/l

Exposure time: 72 h

# **Icosit KC 330 Primer**



Version **Revision Date:** SDS Number: Date of last issue: 2018/12/13 2020/03/01 000000004192 Date of first issue: 2018/12/13 2.0

ethylbenzene:

M-Factor (Acute aquatic tox-

icity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Section 13: Disposal considerations

**Disposal methods** 

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

**Section 14: Transport information** 

**International Regulations** 

**IATA-DGR** 

UN/ID No. UN 1263 Proper shipping name Paint Class 3

Packing group Ш

Labels Flammable Liquids Packing instruction (cargo 366

aircraft)

Packing instruction (passen-

355

ger aircraft)

**IMDG-Code** 

**UN** number UN 1263 Proper shipping name **PAINT** 

10 / 12

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

Class : 3
Packing group : III
Labels : 3

EmS Code : F-E, S-E Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **National Regulations**

#### NZS 5433

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

#### **HSNO Approval Number**

HSR002669

#### **HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

#### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

### **Section 16: Other information**

#### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NZ BEI : New Zealand. Biological Exposure Indices

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

# **Icosit KC 330 Primer**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/12/13

 2.0
 2020/03/01
 000000004192
 Date of first issue: 2018/12/13

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NZ / EN