

## PRODUCT DATA SHEET

# Sika® Aggregate-502

Broadcasting aggregate for flooring applications

### DESCRIPTION

A selection of carefully graded, kiln dried and blended natural aggregates.

### USES

Sika® Aggregate-502 is used as a filler in Sika® resin toppings. It can also be scattered liberally over wet Sikafloor® Systems at a uniform rate to achieve a very coarse textured slip resistant finish. A sealer coat is applied following cure and removal of excess aggregate.

### CHARACTERISTICS / ADVANTAGES

- Compatible with Sikagard® and Sikafloor® flooring and coating systems.
- Provides a very coarse textured, slip-resistant floor finish.

### PRODUCT INFORMATION

<b>Packaging</b>	20 kg bags
<b>Shelf Life</b>	Twenty-four (24) months from date of production if stored in unopened, undamaged and original sealed packaging.
<b>Storage Conditions</b>	Store in dry and cool conditions. Protect from moisture.
<b>Maximum Grain Size</b>	Aggregate grading: 1.18 - 2.8 mm
<b>Density</b>	Dry, bulk density: ~1.5 kg/litre approximately

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

### **Sika (NZ) Limited**

85-91 Patiki Road  
Avondale, Auckland 1026  
New Zealand  
0800 745 269  
www.sika.co.nz



**Product Data Sheet**  
**Sika® Aggregate-502**  
December 2023, Version 01.03  
020816010010000071

SikaAggregate-502-en-NZ-(12-2023)-1-3.pdf

