

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Section 1: Identification

Product name : Sikaflex®-252

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

E-mail address : info@nz.sika.com

Telefax : +64 9 828 4091

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive, For professional users only.

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 4

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity -
single exposure (Inhalation) : Category 2

Specific target organ toxicity -
repeated exposure : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Hazard statements : H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P284 Wear respiratory protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 Store in a well-ventilated place.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
aliphatic prepolymer (t-polyether based)	138626-39-8	>= 1 -< 10
Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-	77703-56-1	>= 2.5 -< 10
aliphatic prepolymer (d-polyether based)	39323-37-0	>= 1 -< 10
xylene	1330-20-7	>= 1 -< 10
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 1 -< 10
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 -< 1
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	85702-90-5	>= 0.1 -< 0.25
dibutyltin dichloride	683-18-1	>= 0.0025 -< 0.025

Section 4: First-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitising effects
Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs if inhaled.

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Carbon dioxide (CO₂)

Unsuitable extinguishing media : Water

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Section 7: Handling and storage

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m ³	NZ OEL
Further information: Ototoxin				
4,4'-methylenediphenyl diisocyanate	101-68-8	WES-TWA (Inhalable Fraction and Vapour)	0.02 mg/m ³ (NCO)	NZ OEL
Further information: Skin sensitiser, Respiratory sensitiser				
		WES-STEL (Inhalable Fraction and Vapour)	0.07 mg/m ³ (NCO)	NZ OEL
dibutyltin dichloride	683-18-1	WES-TWA	0.1 mg/m ³ (Tin)	NZ OEL
Further information: Ototoxin, Skin absorption				
		WES-STEL	0.2 mg/m ³ (Tin)	NZ OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4-Diaminodiphenyl	Urine	End of exposure or end of shift	10 µg/g creatinine	NZ BEI

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
The filter class for the respirator must be suitable for the max-

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : paste
- Colour : various
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : ca. 80 °C (176 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 0.01 hPa
- Relative vapour density : No data available
- Density : ca. 1.21 g/cm³ (20 °C (68 °F))

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds
(VOC) content : 50.7 g/l

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-
tions : No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

dibutyltin dichloride:
Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause damage to organs if inhaled.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

aliphatic prepolymer (t-polyether based):

Toxicity to algae/aquatic plants : EC50 (algae): 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

NOEC (algae): 100 mg/l
Exposure time: 72 h

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Raphidocelis subcapitata (freshwater green alga)): >
plants 100 mg/l
Exposure time: 72 h

aliphatic prepolymer (d-polyether based):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l
aquatic invertebrates
NOEC (Daphnia (water flea)): > 100 mg/l

Toxicity to algae/aquatic : EC50 (algae): > 100 mg/l
plants Exposure time: 72 h

xylene:

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
icity) Exposure time: 56 d

Toxicity to daphnia and other : NOEC (Daphnia (water flea)): 1.17 mg/l
aquatic invertebrates (Chron- Exposure time: 7 d
ic toxicity)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates Exposure time: 48 h

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
plants Exposure time: 72 h
Method: OECD Test Guideline 201

dibutyltin dichloride:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1.4 mg/l
aquatic invertebrates Exposure time: 48 h

M-Factor (Acute aquatic tox- : 10
icity)

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13: Disposal considerations

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Section 14: Transport information

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : Not applicable

Proper shipping name : Not applicable

Class : Not applicable

Subsidiary risk : Not applicable

Packing group : Not applicable

Labels : Not applicable

Packing instruction (cargo aircraft) : Not applicable

Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable

Proper shipping name : Not applicable

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable
Marine pollutant : no

Special precautions for user

Not applicable

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002680

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Revision Date : 2023/08/13
Date format : dd.mm.yyyy

Full text of other abbreviations

NZ BEI : New Zealand. Biological Exposure Indices
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

SAFETY DATA SHEET

Sikaflex®-252



Version
4.0

Revision Date:
2023/08/13

SDS Number:
000000019902

Date of last issue: 2021/08/25
Date of first issue: 2017/10/17

NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

NZ / EN