

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

Section 1: Identification

Product name : Sikafloor-405

Product code : 000000609762

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.
85-91 Patiki Road
Avondale
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

Recommended use of the chemical and restrictions on use

Product use : Polyurethane coating

Section 2: Hazard identification

GHS Classification

Flammable Liquids : 3.1C

Respiratory sensitisation : 6.5A

Skin sensitisation : 6.5B

Toxic to Reproduction : 6.8B

Specific Target Organ Toxicity : 6.9B

Aquatic toxicity (Acute or Chronic) : 9.1B

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

H361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P321 Specific treatment (see supplemental first aid instructions on this label).

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-methoxy-1-methylethyl acetate	108-65-6	>= 20 -< 30
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane-1,2-diylbiscarbamate	59719-67-4	>= 2.5 -< 10
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	>= 0.25 -< 1
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 0.25 -< 1
2-ethylhexanoic acid, zirconium salt	22464-99-9	>= 0.1 -< 1
zinc bis(2-ethylhexanoate)	136-53-8	>= 0.1 -< 0.25
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0.1 -< 0.25
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	64359-81-5	>= 0.1 -< 0.25
2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate, compd. With polyethylene glycol hydrogen	1259547-09-5	>= 0.1 -< 1

Section 4: First-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitising effects
Respiratory disorder
Allergic reactions
Headache
Loss of balance
Vertigo

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

Section 7: Handling and storage

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	WES-TWA	0.02 mg/m ³ (NCO)	NZ OEL
Further information: Sensitiser, Skin absorption, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.				

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

		WES-STEL	0.07 mg/m ³ (NCO)	NZ OEL
--	--	----------	---------------------------------	--------

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : various
- Odour : mild
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : ca. 52 °C (126 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : Upper flammability limit
ca. 10.8 %(V)
(20 °C (68 °F))
- Lower explosion limit / Lower flammability limit : Lower flammability limit

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

flammability limit	ca. 1.5 %(V) (20 °C (68 °F))
Vapour pressure	: 3.1 hPa
Relative vapour density	: No data available
Density	: ca. 1.3 g/cm ³ (20 °C (68 °F))
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: ca. 315 °C (599 °F)
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 1,250 mPa.s
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	: No data available
Oxidizing properties	: No data available

Section 10: Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac- tions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available

Section 11: Toxicological information

Acute toxicity

Not classified based on available information.

Components:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Acute oral toxicity : LD50 Oral (Rat): 1,636 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.26 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Ecotoxicity

Components:

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 87.1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 18.6 mg/l
Exposure time: 72 h

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish : LC50 (Fish): 0.0027 mg/l
Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Section 13: Disposal considerations

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

Section 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint related material
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo : 366
aircraft)
Packing instruction (passen- : 355
ger aircraft)

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : III
Labels : 3

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002662

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

Section 16: Other information

Full text of other abbreviations

NZ OEL	: New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
NZ OEL / WES-TWA	: Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	: Workplace Exposure Standard - Short-Term Exposure Limit
ADG	: Australian Dangerous Goods Code.
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

SAFETY DATA SHEET

Sikafloor-405



Version
2.0

Revision Date:
2021/02/02

SDS Number:
000000609762

Date of last issue: 2019/03/25
Date of first issue: 2019/03/25

NZ / EN